

ResClasses

Set-Theoretic Computations with Residue Classes

Version 2.5.3

September 26, 2007

Stefan Kohl

Stefan Kohl — Email: kohl@mathematik.uni-stuttgart.de
— Homepage: <http://www.cip.mathematik.uni-stuttgart.de/~kohlsn/>
— Address: Institut für Geometrie und Topologie
Pfaffenwaldring 57
Universität Stuttgart
70550 Stuttgart
Germany

Abstract

ResClasses is a package for GAP 4, which provides a fully-featured and easy-to-use implementation of set-theoretic unions of residue classes of the integers and of a few other rings.

The class of sets which ResClasses can deal with includes the open and the closed sets in the topology on the respective ring which is induced by taking the set of all residue classes as a basis, as far as the usual restrictions imposed by the finiteness of computing resources permit this.

The package further provides slightly more specialized functionality for unions of residue classes with distinguished representatives and signed moduli.

The ResClasses package is used in a group theoretical context by the RCWA package [[Koh07](#)].

Copyright

© 2003 - 2007 by Stefan Kohl

This package is distributed under the GNU General Public License.

Contents

1	Set-Theoretic Unions of Residue Classes	5
1.1	Entering residue classes and set-theoretic unions thereof	5
1.1.1	ResidueClass (by ring, modulus and residue)	5
1.1.2	ResidueClassUnion (by ring, modulus and residues)	5
1.1.3	AllResidueClassesModulo (of a given ring, modulo a given modulus)	6
1.2	Methods for residue class unions	7
1.2.1	SplittedClass (for a residue class and a number of parts)	7
1.2.2	AsUnionOfFewClasses (for a residue class union)	8
1.2.3	PartitionsIntoResidueClasses (of a given ring, of given length)	8
1.2.4	RandomPartitionIntoResidueClasses (of a given ring, of given length)	9
1.2.5	Density (of a residue class union)	9
1.3	The categories and families of residue class unions	9
1.3.1	IsResidueClassUnion	9
1.3.2	ResidueClassUnionsFamily (of a ring)	10
2	Unions of Residue Classes with Fixed Representatives	11
2.1	Entering unions of residue classes with fixed representatives	11
2.1.1	ResidueClassWithFixedRepresentative (by ring, modulus and residue)	11
2.1.2	UnionOfResidueClassesWithFixedReps (by ring and list of classes)	11
2.1.3	AllResidueClassesWithFixedRepsModulo (by ring and modulus)	12
2.2	Methods for unions of residue classes with fixed representatives	12
2.2.1	Multiplicity (of an element in a union of residue classes with fixed rep's)	12
2.2.2	Union (for unions of residue classes with fixed representatives)	14
2.2.3	Intersection (for unions of residue classes with fixed representatives)	14
2.2.4	Difference (for unions of residue classes with fixed representatives)	14
2.3	The invariant Delta	15
2.3.1	Delta (for a union of residue classes with fixed representatives)	15
2.3.2	RepresentativeStabilizingRefinement (of a union of res.-classes with fixed rep's)	15
2.4	The categories of unions of residue classes with fixed rep's	15
3	Semilocalizations of the Integers	16
3.1	Entering semilocalizations of the integers	16
3.1.1	Z_pi (by set of noninvertible primes)	16
3.2	Methods for semilocalizations of the integers	16

4	Installation and auxiliary functions	18
4.1	Requirements	18
4.2	Installation	18
4.3	The testing routine	18
4.3.1	ResClassesTest	18
4.4	Building the manual	18
4.4.1	ResClassesBuildManual	18
4.5	SendEmail and EmailLogFile	19
4.5.1	SendEmail	19
4.5.2	EmailLogFile	19

Chapter 1

Set-Theoretic Unions of Residue Classes

1.1 Entering residue classes and set-theoretic unions thereof

1.1.1 ResidueClass (by ring, modulus and residue)

- ◇ `ResidueClass(R, m, r)` (function)
- ◇ `ResidueClass(m, r)` (function)
- ◇ `ResidueClass(r, m)` (function)

Returns: In the three-argument form the residue class $r \bmod m$ of the ring R , and in the two-argument form the residue class $r \bmod m$ of the “default ring” (\rightarrow `DefaultRing` in the GAP Reference Manual) of the arguments.

In the two-argument case, m is taken to be the larger and r is taken to be the smaller of the arguments. For convenience, it is permitted to enclose the argument list in list brackets.

Residue classes have the property `IsResidueClass`. Rings are regarded as residue class $0 \pmod{1}$, and therefore have this property. There are operations `Modulus` and `Residue` to retrieve the modulus m resp. residue r of a residue class.

Example

```
gap> ResidueClass(2,3);
The residue class 2(3) of Z
gap> ResidueClass(Z_pi([2,5]),2,1);
The residue class 1(2) of Z_( 2, 5 )
gap> R := PolynomialRing(GF(2),1);;
gap> x := Indeterminate(GF(2),1);; SetName(x,"x");
gap> ResidueClass(R,x+One(R),Zero(R));
The residue class 0*Z(2) ( mod x+Z(2)^0 ) of GF(2)[x]
```

1.1.2 ResidueClassUnion (by ring, modulus and residues)

- ◇ `ResidueClassUnion(R, m, r)` (function)
- ◇ `ResidueClassUnion(R, m, r, included, excluded)` (function)

Returns: The union of the residue classes $r[i] \bmod m$ of the ring R , plus / minus finite sets *included* and *excluded* of elements of R .

Example

```
gap> ResidueClassUnion(Integers,5,[1,2],[3,8],[-4,1]);
(Union of the residue classes 1(5) and 2(5) of Z) U [ 3, 8 ] \ [ -4, 1 ]
gap> ResidueClassUnion(Z_pi([2,3]),8,[3,5]);
Union of the residue classes 3(8) and 5(8) of Z_( 2, 3 )
gap> ResidueClassUnion(R,x^2,[One(R),x],[],[One(R)]);
<union of 2 residue classes (mod x^2) of GF(2)[x]> \ [ Z(2)^0 ]
```

When talking about a *residue class union* in this chapter, we always mean an object as it is returned by this function.

There are operations `Modulus`, `Residues`, `IncludedElements` and `ExcludedElements` to retrieve the components of a residue class union as they have originally been passed as arguments to `ResidueClassUnion` (1.1.2).

The user has the choice between a longer and more descriptive and a shorter and less bulky output format for residue classes and unions thereof:

Example

```
gap> ResidueClassUnionViewingFormat("short");
gap> ResidueClassUnion(Integers,12,[0,1,4,7,8]);
0(4) U 1(6)
gap> ResidueClassUnionViewingFormat("long");
gap> ResidueClassUnion(Integers,12,[0,1,4,7,8]);
Union of the residue classes 0(4) and 1(6) of Z
```

1.1.3 AllResidueClassesModulo (of a given ring, modulo a given modulus)

◇ `AllResidueClassesModulo(R, m)` (function)

◇ `AllResidueClassesModulo(m)` (function)

Returns: A sorted list of all residue classes (mod m) of the ring R .

If the argument R is omitted it defaults to the default ring of m – cf. the documentation of `DefaultRing` in the GAP reference manual. A transversal for the residue classes (mod m) can be obtained by the operation `AllResidues(R, m)`, and their number can be determined by the operation `NumberOfResidues(R, m)`.

Example

```
gap> AllResidueClassesModulo(Integers,2);
[ The residue class 0(2) of Z, The residue class 1(2) of Z ]
gap> AllResidueClassesModulo(Z_pi(2),2);
[ The residue class 0(2) of Z_( 2 ), The residue class 1(2) of Z_( 2 ) ]
gap> AllResidueClassesModulo(R,x);
[ The residue class 0*Z(2) (mod x) of GF(2)[x],
  The residue class Z(2)^0 (mod x) of GF(2)[x] ]
gap> AllResidues(R,x^3);
[ 0*Z(2), Z(2)^0, x, x+Z(2)^0, x^2, x^2+Z(2)^0, x^2+x, x^2+x+Z(2)^0 ]
gap> NumberOfResidues(Z_pi([2,3]),360);
72
```

1.2 Methods for residue class unions

There are methods for `Print`, `String` and `Display` which are applicable to residue class unions. There is a method for `in` which tests whether some ring element lies in a given residue class union.

Example

```
gap> Print(ResidueClass(1,2),"\n");
ResidueClassUnion( Integers, 2, [ 1 ] )
gap> 1 in ResidueClass(1,2);
true
```

There are methods for `Union`, `Intersection`, `Difference` and `IsSubset` available for residue class unions. They also accept finite subsets of the base ring as arguments.

Example

```
gap> S := Union(ResidueClass(0,2),ResidueClass(0,3));
Z \ Union of the residue classes 1(6) and 5(6) of Z
gap> Intersection(S,ResidueClass(0,7));
Union of the residue classes 0(14) and 21(42) of Z
gap> Difference(S,ResidueClass(2,4));
Union of the residue classes 0(4) and 3(6) of Z
gap> IsSubset(ResidueClass(0,2),ResidueClass(4,8));
true
gap> Union(S,[1..10]);
(Union of the residue classes 0(2) and 3(6) of Z) U [ 1, 5, 7 ]
gap> Intersection(S,[1..6]);
[ 2, 3, 4, 6 ]
gap> Difference(S,[1..6]);
(Union of the residue classes 0(2) and 3(6) of Z) \ [ 2, 3, 4, 6 ]
gap> Difference(Integers,[1..10]);
Z \ <set of cardinality 10>
gap> IsSubset(S,[1..10]);
false
```

If the underlying ring has a residue class ring of a given cardinality t , then a residue class can be written as a disjoint union of t residue classes with equal moduli:

1.2.1 SplittedClass (for a residue class and a number of parts)

◇ `SplittedClass(cI , t)`

(operation)

Returns: A partition of the residue class cI into t residue classes with equal moduli, provided that such a partition exists. Otherwise fail.

Example

```
gap> SplittedClass(ResidueClass(1,2),2);
[ The residue class 1(4) of Z, The residue class 3(4) of Z ]
gap> SplittedClass(ResidueClass(Z_pi(3),3,0),2);
fail
```

Often one needs a partition of a given residue class union into “few” residue classes. The following operation takes care of this:

1.2.2 AsUnionOfFewClasses (for a residue class union)

◇ `AsUnionOfFewClasses(U)` (operation)

Returns: A set of disjoint residue classes whose union is equal to U , up to the finite sets `IncludedElements(U)` and `ExcludedElements(U)`.

As the name of the operation suggests, it is taken care that the number of residue classes in the returned list is kept “reasonably small”. It is not guaranteed that it is minimal.

Example

```
gap> ResidueClassUnionViewingFormat("short");
gap> AsUnionOfFewClasses(Difference(Integers,ResidueClass(0,30)));
[ 1(2), 2(6), 4(6), 6(30), 12(30), 18(30), 24(30) ]
gap> Union(last);
Z \ 0(30)
```

One can compute the sets of sums, differences, products and quotients of the elements of a residue class union and an element of the base ring:

Example

```
gap> ResidueClass(0,2) + 1;
1(2)
gap> ResidueClass(0,2) - 2 = ResidueClass(0,2);
true
gap> 3 * ResidueClass(0,2);
0(6)
gap> ResidueClass(0,2)/2;
Integers
```

1.2.3 PartitionsIntoResidueClasses (of a given ring, of given length)

◇ `PartitionsIntoResidueClasses(R , $length$)` (operation)

Returns: A sorted list of all partitions of the ring R into $length$ residue classes.

Example

```
gap> PartitionsIntoResidueClasses(Integers,4);
[ [ 0(2), 1(4), 3(8), 7(8) ], [ 0(2), 3(4), 1(8), 5(8) ],
  [ 0(2), 1(6), 3(6), 5(6) ], [ 1(2), 0(4), 2(8), 6(8) ],
  [ 1(2), 2(4), 0(8), 4(8) ], [ 1(2), 0(6), 2(6), 4(6) ],
  [ 0(3), 1(3), 2(6), 5(6) ], [ 0(3), 2(3), 1(6), 4(6) ],
  [ 1(3), 2(3), 0(6), 3(6) ], [ 0(4), 1(4), 2(4), 3(4) ] ]
```

1.2.4 RandomPartitionIntoResidueClasses (of a given ring, of given length)

◇ `RandomPartitionIntoResidueClasses(R , $length$, $primes$)` (operation)

Returns: A “random” partition of the ring R into $length$ residue classes whose moduli have only prime factors in $primes$, respectively fail if no such partition exists.

Example

```
gap> RandomPartitionIntoResidueClasses(Integers,30,[2,3,5,7]);
[ 0(7), 2(7), 5(7), 3(14), 10(14), 1(21), 8(21), 15(21), 18(21), 20(21),
  6(63), 13(63), 25(63), 27(63), 32(63), 34(63), 46(63), 48(63), 53(63),
  55(63), 4(126), 67(126), 137(189), 74(567), 200(567), 263(567),
  389(567), 452(567), 11(1134), 578(1134) ]
gap> Union(last);
Integers
gap> Sum(List(last2,Density));
1
```

1.2.5 Density (of a residue class union)

◇ `Density(U)` (operation)

Returns: The natural density of U as a subset of the underlying ring.

The *natural density* of a residue class $r(m)$ of a ring R is defined by $1/|R/mR|$, and the *natural density* of a union U of finitely many residue classes is defined by the sum of the densities of the elements of a partition of U into finitely many residue classes.

Example

```
gap> Density(ResidueClass(0,2));
1/2
gap> Density(Difference(Integers,ResidueClass(0,5)));
4/5
```

For looping over residue class unions of the integers, there are methods for the operations `Iterator` and `NextIterator`.

1.3 The categories and families of residue class unions

1.3.1 IsResidueClassUnion

◇ `IsResidueClassUnion(U)` (filter)

◇ `IsResidueClassUnionOfZ(U)` (filter)

◇ `IsResidueClassUnionOfZ_pi(U)` (filter)

◇ `IsResidueClassUnionOfGFqx(U)` (filter)

Returns: `true` if U is a residue class union, a residue class union of the ring of integers, a residue class union of a semilocalization of the ring of integers or a residue class union of a polynomial ring in one variable over a finite field, respectively, and `false` otherwise.

Often the same methods can be used for residue class unions of the ring of integers and of its semilocalizations. For this reason, there is a category `IsResidueClassUnionOfZorZ_pi` which is

the union of `IsResidueClassUnionOfZ` and `IsResidueClassUnionOfZ_pi`. The internal representation of residue class unions is called `IsResidueClassUnionResidueListRep`. There are methods available for `ExtRepOfObj` and `ObjByExtRep`.

1.3.2 ResidueClassUnionsFamily (of a ring)

◇ `ResidueClassUnionsFamily(R)` (function)

◇ `ResidueClassUnionsFamily(R , fixedreps)` (function)

Returns: The family of residue class unions or the family of unions of residue classes with fixed representatives of the ring R , depending on whether *fixedreps* is present and `true` or not.

The ring R can be retrieved as `UnderlyingRing(ResidueClassUnionsFamily(R))`. There is no coercion between residue class unions or unions of residue classes with fixed representatives which belong to different families. Unions of residue classes with fixed representatives are described in the next chapter.

Chapter 2

Unions of Residue Classes with Fixed Representatives

ResClasses supports computations with unions of residue classes which are endowed with distinguished (“fixed”) representatives. These unions of residue classes can be viewed as multisets of ring elements. The residue classes forming such a union do not need to be disjoint or even only distinct.

2.1 Entering unions of residue classes with fixed representatives

2.1.1 ResidueClassWithFixedRepresentative (by ring, modulus and residue)

- ◇ `ResidueClassWithFixedRepresentative(R, m, r)` (function)
- ◇ `ResidueClassWithFixedRepresentative(m, r)` (function)

Returns: The residue class $r \bmod m$ of the ring R , with the fixed representative r .

If the argument R is omitted, it defaults to `Integers`. Residue classes with fixed representatives have the property `IsResidueClassWithFixedRepresentative`. The fixed representative r can be retrieved by the operation `Residue`, and the modulus m can be retrieved by the operation `Modulus`.

Example

```
gap> ResidueClassWithFixedRepresentative(Integers,2,1);  
[1/2]
```

2.1.2 UnionOfResidueClassesWithFixedReps (by ring and list of classes)

- ◇ `UnionOfResidueClassesWithFixedReps(R, classes)` (function)
- ◇ `UnionOfResidueClassesWithFixedReps(classes)` (function)

Returns: The union of the residue classes $classes[i][2] \bmod classes[i][1]$ of the ring R , with fixed representatives $classes[i][2]$.

The argument $classes$ must be a list of pairs of elements of the ring R . Their first entries – the moduli – must be nonzero. If the argument R is omitted, it defaults to `Integers`.

Example

```
gap> UnionOfResidueClassesWithFixedReps(Integers, [[2,4], [3,9]]);
[4/2] U [9/3]
```

There is a method for the operation `Modulus` which returns the lcm of the moduli of the residue classes forming such a union. Further there is an operation `Classes` for retrieving the list of classes which has been passed as an argument to `UnionOfResidueClassesWithFixedReps`. The operation `AsListOfClasses` does the same, except that the returned list contains residue classes instead of pairs $[modulus, residue]$. There are methods for `Print`, `String` and `Display` available for unions of residue classes with fixed representatives.

2.1.3 AllResidueClassesWithFixedRepsModulo (by ring and modulus)

◇ `AllResidueClassesWithFixedRepsModulo(R , m)` (function)

◇ `AllResidueClassesWithFixedRepsModulo(m)` (function)

Returns: A sorted list of all residue classes (mod m) of the ring R , with fixed representatives.

If the argument R is omitted it defaults to the default ring of m , cf. the documentation of `DefaultRing` in the GAP reference manual. The representatives are the same as those chosen by the operation `mod`. See also `AllResidueClassesModulo` (1.1.3).

Example

```
gap> AllResidueClassesWithFixedRepsModulo(4);
[ [0/4], [1/4], [2/4], [3/4] ]
```

2.2 Methods for unions of residue classes with fixed representatives

Throughout this chapter, the argument R denotes the underlying ring, and the arguments U , $U1$ and $U2$ denote unions of residue classes of R with fixed representatives.

Unions of residue classes with fixed representatives are multisets. Elements and residue classes can be contained with multiplicities:

2.2.1 Multiplicity (of an element in a union of residue classes with fixed rep's)

◇ `Multiplicity(x , U)` (method)

◇ `Multiplicity($c1$, U)` (method)

Returns: The multiplicity of x in U regarded as a multiset of ring elements, resp. the multiplicity of the residue class $c1$ in U regarded as a multiset of residue classes.

Example

```
gap> U := UnionOfResidueClassesWithFixedReps(Integers, [[2,0], [3,0]]);
[0/2] U [0/3]
gap> List([0..20], n->Multiplicity(n,U));
[ 2, 0, 1, 1, 1, 0, 2, 0, 1, 1, 1, 0, 2, 0, 1, 1, 1, 0, 2, 0, 1 ]
gap> Multiplicity(ResidueClassWithFixedRep(2,0),U);
1
```

Let U be a union of residue classes with fixed representatives. The multiset U can have an attribute `Density` which denotes its *natural density* as a multiset, i.e. elements with multiplicity k count k -fold. The multiset U has the property `IsOverlappingFree` if it consists of pairwise disjoint residue classes. The set-theoretic union of the residue classes forming U can be determined by the operation `AsOrdinaryUnionOfResidueClasses`. The object returned by this operation is an “ordinary” residue class union as described in Chapter 1.

Example

```
gap> U := UnionOfResidueClassesWithFixedReps(Integers, [[2,0],[3,0]]);
[0/2] U [0/3]
gap> Density(U);
5/6
gap> IsOverlappingFree(U);
false
gap> AsOrdinaryUnionOfResidueClasses(U);
Z \ Union of the residue classes 1(6) and 5(6) of Z
gap> Density(last);
2/3
```

In the sequel we abbreviate the term “the multiset of ring elements endowed with the structure of a union of residue classes with fixed representatives” by “the multiset”.

There are methods for `+` and `-` available for computing the multiset of sums $u+x$, $u \in U$, the multiset of differences $u-x$ resp. $x-u$, $u \in U$ and the multiset of the additive inverses of the elements of U . Further there are methods for `*` and `/` available for computing the multiset of products $x \cdot u$, $u \in U$ and the multiset of quotients u/x , $u \in U$. The division method requires all elements of U to be divisible by x . If the underlying ring is the ring of integers, scalar multiplication and division leave δ invariant (\rightarrow Delta (2.3.1)).

Example

```
gap> U := UnionOfResidueClassesWithFixedReps(Integers, [[2,0],[3,0]]);
[0/2] U [0/3]
gap> U + 7;
[7/2] U [7/3]
gap> U - 7; 7 - U; -U;
[-7/2] U [-7/3]
[7/-3] U [7/-2]
[0/-3] U [0/-2]
gap> V := 2 * U;
[0/4] U [0/6]
gap> V/2;
[0/2] U [0/3]
```

2.2.2 Union (for unions of residue classes with fixed representatives)

◇ `Union($U1$, $U2$)`

(method)

Returns: The union of $U1$ and $U2$.

The multiplicity of any ring element or residue class in the union is the sum of its multiplicities in the arguments. It holds that $\text{Delta}(\text{Union}(U1, U2)) = \text{Delta}(U1) + \text{Delta}(U2)$. (\rightarrow Delta (2.3.1)).

Example

```
gap> U := UnionOfResidueClassesWithFixedReps(Integers, [[2,0],[3,0]]);
[0/2] U [0/3]
gap> Union(U,U);
[0/2] U [0/2] U [0/3] U [0/3]
```

2.2.3 Intersection (for unions of residue classes with fixed representatives)

◇ `Intersection($U1$, $U2$)`

(method)

Returns: The intersection of $U1$ and $U2$.

The multiplicity of any residue class in the intersection is the minimum of its multiplicities in the arguments.

Example

```
gap> U := UnionOfResidueClassesWithFixedReps(Integers, [[2,0],[3,0]]);
[0/2] U [0/3]
gap> Intersection(U, ResidueClassWithFixedRep(2,0));
[0/2]
gap> Intersection(U, ResidueClassWithFixedRep(6,0));
Empty union of residue classes of Z with fixed representatives
```

2.2.4 Difference (for unions of residue classes with fixed representatives)

◇ `Difference($U1$, $U2$)`

(method)

Returns: The difference of $U1$ and $U2$.

The multiplicity of any residue class in the difference is its multiplicity in $U1$ minus its multiplicity in $U2$, if this value is nonnegative. The difference of the empty residue class union with fixed representatives and some residue class $[r/m]$ is set equal to $[(m-r)/m]$. It holds that $\text{Delta}(\text{Difference}(U1, U2)) = \text{Delta}(U1) - \text{Delta}(U2)$. (\rightarrow Delta (2.3.1)).

Example

```
gap> U := UnionOfResidueClassesWithFixedReps(Integers, [[2,0],[3,0]]);
[0/2] U [0/3]
gap> V := UnionOfResidueClassesWithFixedReps(Integers, [[3,0],[5,2]]);
[0/3] U [2/5]
gap> Difference(U,V);
[0/2] U [3/5]
```

2.3 The invariant Delta

2.3.1 Delta (for a union of residue classes with fixed representatives)

◇ `Delta(U)` (attribute)

Returns: The value of the invariant δ of the residue class union U .

For a residue class $[r/m]$ with fixed representative we set $\delta([r/m]) := r/m - 1/2$, and extend this definition additively to unions of such residue classes. If no representatives are fixed, this definition is still unique (mod 1). There is a related invariant ρ which is defined by $e^{\delta(U)\pi i}$. The corresponding attribute is called Rho.

Example

```
gap> U := UnionOfResidueClassesWithFixedReps(Integers, [[2, 3], [3, 4]]);
[3/2] U [4/3]
gap> Delta(U) = (3/2-1/2) + (4/3-1/2);
true
gap> V := RepresentativeStabilizingRefinement(U, 3);
[3/6] U [5/6] U [7/6] U [4/9] U [7/9] U [10/9]
gap> Delta(V) = Delta(U);
true
gap> Rho(V);
E(12)^11
```

2.3.2 RepresentativeStabilizingRefinement (of a union of res.-classes with fixed rep's)

◇ `RepresentativeStabilizingRefinement(U, k)` (method)

Returns: The representative stabilizing refinement of U into k parts.

The *representative stabilizing refinement* of a residue class $[r/m]$ of \mathbb{Z} into k parts is defined by $[r/km] \cup [(r+m)/km] \cup \dots \cup [(r+(k-1)m)/km]$. This definition is extended in the obvious way to unions of residue classes.

If the argument k is zero, the method performs a simplification of U by joining appropriate residue classes, if this is possible.

In any case the value of `Delta(U)` is invariant under this operation (\rightarrow `Delta(2.3.1)`).

Example

```
gap> U := UnionOfResidueClassesWithFixedReps(Integers, [[2, 0], [3, 0]]);
[0/2] U [0/3]
gap> RepresentativeStabilizingRefinement(U, 4);
[0/8] U [2/8] U [4/8] U [6/8] U [0/12] U [3/12] U [6/12] U [9/12]
gap> RepresentativeStabilizingRefinement(last, 0);
[0/2] U [0/3]
```

2.4 The categories of unions of residue classes with fixed rep's

The names of the categories of unions of residue classes with fixed representatives are `IsUnionOfResidueClasses[OfZ | OfZ_pi | OfZorZ_pi | OfGFqx]WithFixedRepresentatives`.

Chapter 3

Semilocalizations of the Integers

This package implements residue class unions of the semilocalizations $\mathbb{Z}_{(\pi)}$ of the ring of integers. It also provides the underlying GAP implementation of these rings themselves.

3.1 Entering semilocalizations of the integers

3.1.1 `Z_pi` (by set of noninvertible primes)

◇ `Z_pi(pi)` (function)

◇ `Z_pi(p)` (function)

Returns: The ring $\mathbb{Z}_{(\pi)}$ or the ring $\mathbb{Z}_{(p)}$, respectively.

The returned ring has the property `IsZ_pi`. The set `pi` of noninvertible primes can be retrieved by the operation `NoninvertiblePrimes`.

Example

```
gap> R := Z_pi(2);
Z_( 2 )
gap> S := Z_pi([2,5,7]);
Z_( 2, 5, 7 )
```

3.2 Methods for semilocalizations of the integers

There are methods for the operations `in`, `Intersection`, `IsSubset`, `StandardAssociate`, `Gcd`, `Lcm`, `Factors` and `IsUnit` available for semilocalizations of the integers. For the documentation of these operations, see the GAP reference manual. The standard associate of an element of a ring $\mathbb{Z}_{(\pi)}$ is defined by the product of the noninvertible prime factors of its numerator.

Example

```
gap> 4/7 in R; 3/2 in R;
true
false
gap> Intersection(R, Z_pi([3,11])); IsSubset(R, S);
Z_( 2, 3, 11 )
true
```

Example

```
gap> StandardAssociate(R, -6/7);  
2  
gap> Gcd(S, 90/3, 60/17, 120/33);  
10  
gap> Lcm(S, 90/3, 60/17, 120/33);  
40  
gap> Factors(R, 840);  
[ 105, 2, 2, 2 ]  
gap> Factors(R, -2/3);  
[ -1/3, 2 ]  
gap> IsUnit(S, 3/11);  
true
```

Chapter 4

Installation and auxiliary functions

4.1 Requirements

The ResClasses package needs at least GAP 4.4.7 and GAPDoc 0.99999 [LN07]. It can be used under UNIX, under Windows and on the MacIntosh. ResClasses is completely written in the GAP language and does neither contain nor require external binaries.

4.2 Installation

Like any other GAP package, ResClasses must be installed in the `pkg` subdirectory of the GAP distribution. This is accomplished by extracting the distribution file in this directory. By default, the package ResClasses is autoloading. If you have switched autoloading of packages off, you can load ResClasses via `LoadPackage("resclasses");`.

4.3 The testing routine

4.3.1 ResClassesTest

◇ `ResClassesTest()` (function)

Returns: Nothing.

Performs tests of the ResClasses package. Errors, i.e. differences to the correct results of the test computations, are reported. The processed test files are in the directory `pkg/resclasses/tst`.

4.4 Building the manual

4.4.1 ResClassesBuildManual

◇ `ResClassesBuildManual()` (function)

Returns: Nothing.

This function is a development tool which builds the manual of the ResClasses package in the file formats \LaTeX , PDF, HTML and ASCII text. This is accomplished using the GAPDoc package by Frank Lübeck and Max Neunhoffer. Building the manual is possible only on UNIX systems and requires PDF \LaTeX . As all files generated by this function are included in the distribution file anyway, users will not need it.

4.5 SendEmail and EmailLogFile

4.5.1 SendEmail

◇ `SendEmail(sendto, copyto, subject, text)` (function)

Returns: Zero if everything worked correctly, and a system error number otherwise.

Sends an e-mail with subject *subject* and body *text* to the addresses in the list *sendto*, and copies it to those in the list *copyto*. The first two arguments must be lists of strings, and the latter two must be strings.

As most system-related functions, `SendEmail` works only under UNIX. Further, the computer must of course be connected to the internet.

4.5.2 EmailLogFile

◇ `EmailLogFile(addresses)` (function)

Returns: Zero if everything worked correctly, and a system error number otherwise.

Sends the current log file by e-mail to *addresses*, if GAP is in logging mode and one is working under UNIX, and does nothing otherwise. The argument *addresses* must be either a list of e-mail addresses or a single e-mail address. Long log files are abbreviated, i.e. if the log file is larger than 64KB, then any output is truncated at 1KB, and if the log file is still longer than 64KB afterwards, it is truncated at 64KB.

References

- [Koh07] S. Kohl. *RCWA - Residue-Class-Wise Affine Groups (Version 2.5)*, 2007. GAP package, <http://www.gap-system.org/Packages/rcwa.html>. 2
- [LN07] F. Lübeck and M. Neunhöffer. *GAPDoc (Version 1.0)*. RWTH Aachen, 2007. GAP package, <http://www.gap-system.org/Packages/gapdoc.html>. 18

Index

- AllResidueClassesModulo
 - by modulus, of the default ring of that modulus, [6](#)
 - of a given ring, modulo a given modulus, [6](#)
- AllResidueClassesWithFixedRepsModulo
 - by modulus, of the default ring of that modulus, [12](#)
 - by ring and modulus, [12](#)
- AllResidues
 - by ring and modulus, [6](#)
- AsListOfClasses
 - for a union of residue classes with fixed rep's, [12](#)
- AsOrdinaryUnionOfResidueClasses
 - for a union of residue classes with fixed rep's, [13](#)
- AsUnionOfFewClasses
 - for a residue class union, [8](#)
- Classes
 - of a union of residue classes with fixed rep's, [12](#)
- Delta
 - for a union of residue classes with fixed representatives, [15](#)
- Density
 - of a residue class union, [9](#)
- Density
 - of a union of residue classes with fixed rep's, [13](#)
- Difference
 - for unions of residue classes with fixed representatives, [14](#)
- Difference
 - for residue class unions, [7](#)
- Display
 - for a residue class union, [7](#)
- EmailLogFile, [19](#)
- ExcludedElements
 - of a residue class union, [6](#)
- ExtRepOfObj, [10](#)
- Factors
 - of an element of a semilocalization of Z , [16](#)
- Gcd
 - of elements of a semilocalization of Z , [16](#)
- IncludedElements
 - of a residue class union, [6](#)
- Intersection
 - for unions of residue classes with fixed representatives, [14](#)
- Intersection
 - for residue class unions, [7](#)
- IsOverlappingFree
 - for a union of residue classes with fixed rep's, [13](#)
- IsResidueClass, [5](#)
- IsResidueClassUnion, [9](#)
- IsResidueClassUnionOfGFqx, [9](#)
- IsResidueClassUnionOfZ, [9](#)
- IsResidueClassUnionOfZ_pi, [10](#)
- IsResidueClassUnionOfZ_pi, [9](#)
- IsResidueClassUnionResidueListRep, [10](#)
- IsResidueClassWithFixedRep, [11](#)
- IsSubset
 - for residue class unions, [7](#)
- IsUnit
 - for an element of a semilocalization of Z , [16](#)
- IsZ_pi, [16](#)
- Iterator
 - for a residue class union, [9](#)
- Lcm

- of elements of a semilocalization of Z , 16
- Modulus
 - of a residue class, 5
 - of a residue class union, 6
 - of a union of residue classes with fixed rep's, 12
- Multiplicity
 - of a residue class in a union of residue classes with fixed rep's, 12
 - of an element in a union of residue classes with fixed rep's, 12
- NextIterator
 - for an iterator of a residue class union, 9
- NoninvertiblePrimes
 - of a semilocalization of Z , 16
- NumberOfResidues
 - by ring and modulus, 6
- ObjByExtRep, 10
- PartitionsIntoResidueClasses
 - of a given ring, of given length, 8
- Print
 - for a residue class union, 7
- RandomPartitionIntoResidueClasses
 - of a given ring, of given length, 9
- RepresentativeStabilizingRefinement
 - of a union of res.-classes with fixed rep's, 15
- ResClassesBuildManual, 18
- ResClassesTest, 18
- Residue
 - of a residue class, 5
- residue class union
 - coercion, 10
 - definition, 6
- ResidueClass
 - by modulus and residue, 5
 - by residue and modulus, 5
 - by ring, modulus and residue, 5
- ResidueClassUnion
 - by ring, modulus and residues, 5
 - dito, plus included / excluded elements, 5
- ResidueClassUnionsFamily
 - of a ring, 10
 - of a ring, with fixed representatives, 10
- ResidueClassUnionViewingFormat, 6
- ResidueClassWithFixedRepresentative
 - by ring, modulus and residue, 11
 - of Z , by modulus and residue, 11
- Residues
 - of a residue class union, 6
- Rho
 - for a union of residue classes with fixed rep's, 15
- SendEmail, 19
- SplittedClass
 - for a residue class and a number of parts, 7
- StandardAssociate
 - of an element of a semilocalization of Z , 16
- String
 - for a residue class union, 7
- Union
 - for unions of residue classes with fixed representatives, 14
- Union
 - for residue class unions, 7
- UnionOfResidueClassesWithFixedReps
 - by ring and list of classes, 11
 - of Z , by list of classes, 11
- Z_{π}
 - by noninvertible prime, 16
 - by set of noninvertible primes, 16