

The automultiplechoice package*

Alexis Bienvenue
paamc@passoire.fr

March 5, 2012

Abstract

This package helps designing multiple choice exams ready for automated marking from papers scans.

Answers and questions are optionally shuffled, creating different sheets for every student.

1 Introduction

The package `automultiplechoice` helps formatting multiple choice questionnaires with automated marking from papers scans in mind:

- The package can produce different copies of the question sheet for each student, optionally shuffling answers and questions for each student.
- Markers can be printed on each sheet, so as to be able to analyse scans after examination. All the needed information about the position of the markers and the boxes to be checked by the students is given in an auxiliary file during \LaTeX run.

See Auto Multiple Choice (AMC) software (<http://home.gna.org/auto-qcm/>) for an integration of this package, with user interface for automated marking.

2 Samples

We begin with several samples to see what can be done with the `automultiplechoice` package. All `automultiplechoice` commands and options will be detailed further.

For all these samples, two sets of questions are used: a group of geography questions, and a group of history questions. These are defined in a common \LaTeX file named `questions.tex`:

```
\element{geography}{  
  \begin{question}{Ghana}  
    What is the capital of Ghana?  
    \begin{choiceshoriz}
```

*This document corresponds to version *Revision* : 431 from AMC 1.0.3

```

        \correctchoice{Accra}
        \wrongchoice{Addis Abeba}
        \wrongchoice{Ankara}
        \wrongchoice{Apia}
    \end{choiceshoriz}
\end{question}
}

\element{geography}{
    \begin{question}{Thailand}
        What is the capital of Thailand?
        \begin{choiceshoriz}
            \correctchoice{Bangkok}
            \wrongchoice{Banjul}
            \wrongchoice{Beijing}
            \wrongchoice{Beirut}
            \wrongchoice{Berlin}
        \end{choiceshoriz}
    \end{question}
}

\element{geography}{
    \begin{question}{Egypt}
        What is the capital of Egypt?
        \begin{choices}
            \correctchoice{Cairo}
            \wrongchoice{Caracas}
            \wrongchoice{Cayenne}
            \wrongchoice{Chisinau}
            \wrongchoice{Conakry}
        \end{choices}
    \end{question}
}

\element{geography}{
    \begin{question}{Ireland}
        What is the capital of Ireland?
        \begin{multicols}{3}
            \begin{choices}
                \correctchoice{Dublin}
                \wrongchoice{Dili}
                \wrongchoice{Djibouti}
                \wrongchoice{Doha}
                \wrongchoice{Dakar}
                \wrongchoice{Dhaka}
            \end{choices}

```

```

        \end{multicols}
    \end{question}
}

\element{history}{
    \begin{questionmult}{1901}
        Which of the following events are taking place during the year
        1901?
        \begin{choices}
            \correctchoice{Funeral of Queen Victoria in London}
            \correctchoice{Official end of the Caste War of Yucat'an}
            \wrongchoice{King George of Greece becomes absolute monarch of Crete}
            \wrongchoice{The first line of the Paris M'etro is opened}
        \end{choices}
    \end{questionmult}
}

\element{history}{
    \begin{questionmult}{1850}
        Which of the following events are taking place during the year
        1850?
        \begin{choices}
            \correctchoice{American Express is founded by Henry Wells \& William Fargo}
            \wrongchoice{Napoleon Bonaparte crosses the Alps and invades Italy}
            \wrongchoice{Kwang-su becomes emperor of China}
            \wrongchoice{First horse-drawn omnibuses established in London}
        \end{choices}
    \end{questionmult}
}

\element{history}{
    \begin{questionmult}{1971}
        Which of the following events are taking place during the year
        1971?
        \begin{choices}
            \correctchoice{Apollo 14 lands on the Moon}
            \correctchoice{The Soviet Union launches Salyut 1}
            \correctchoice{Death of Louis Armstrong}
            \wrongchoice{The first commercial Concorde flight takes off}
        \end{choices}
    \end{questionmult}
}

```

We will ask automultiplechoice package to include two geography questions and two history questions at random for each student, shuffling questions and answers, with the following code:

```
\cleargroup{all}
```

```

\shufflegroup{geography}
\copygroup[2]{geography}{all}
\shufflegroup{history}
\copygroup[2]{history}{all}
\shufflegroup{all}
\insertgroup{all}

```

You can read these commands as “clear group `all`, shuffle questions inside group `geography` and copy the first two to group `all`, do the same for group `history`, shuffle the four questions copied into `all` and print them”.

2.1 Standard layout

A set of 30 students sheets can be produced from the following L^AT_EX source named `sample-amc.tex`:

```

\documentclass{article}
\usepackage{automultiplechoice}
\usepackage{multicol}
\begin{document}

\input{questions.tex}

\onecopy{30}{

\noindent{\bf AMC \hfill SAMPLE TEST}

\vspace{3ex}

```

For this test, package `{\sf automultiplechoice}` is used without any option. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `{\tt nowatermark}` option.

Commands from `{\sf automultiplechoice}` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

```

\vspace{3ex}

\cleargroup{all}

\shufflegroup{geography}
\copygroup[2]{geography}{all}
\shufflegroup{history}
\copygroup[2]{history}{all}
\shufflegroup{all}
\insertgroup{all}

```

```
}
\end{document}
```

producing a 30-pages document (every page has number 1), from which we show the first pages on page 8.

Note that “DRAFT” indications can be cancelled using option `nowatermark`, or using AMC software.

You can see on each page markers that can be used for automated completed answer sheets scans analysis:

- Four circles ● are printed in the corners, to be able to analyse any rotation or scaling of the scans.
- Binary boxes are printed in the header area, so as to be able to read student sheet number and page number. On page 2 for example, you can see that these binary boxes are coding 2/1/59:



Here, 2 is the student sheet number, 1 is the page number for this student, and 59 is a checking value that can be used for checking correct identification from a scan.

If you also use `calibration` option, `automultiplechoice` will produce a `.xy` file with informations about the exact position in the page of all the markers, and all the boxes. This option is automatically set by AMC software, which then use the information in the `.xy` file for automated marking.

2.2 Separate answer sheet

In some situations, you may need a separate answer sheet:

- this makes cheating even more difficult;
- this can reduce the number of pages to scan.

This is done using `separateanswersheet` option of `automultiplechoice` package. You also have to use commands `\AMCformBegin` to indicate the beginning of this separate answer sheet (usually after a `\clearpage` or `\AMCcleardoublepage` command), and `\AMCform` to insert the form to be completed by the students, as in the following example (`sample-separate.tex`):

```
\documentclass{article}
\usepackage[separateanswersheet]{automultiplechoice}
\usepackage{multicol}
\begin{document}

\input{questions.tex}

\onecopy{30}{
```

```
\noindent{\bf AMC \hfill SAMPLE TEST}
```

```
\vspace{3ex}
```

For this test, package {\sf automultiplechoice} is used with {\tt separateanswersheet} option, so that all answers are to be filled on a separate sheet by students. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using {\tt nowatermark} option.

Commands from {\sf automultiplechoice} are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

```
\vspace{3ex}
```

```
\cleargroup{all}
```

```
\shufflegroup{geography}
```

```
\copygroup[2]{geography}{all}
```

```
\shufflegroup{history}
```

```
\copygroup[2]{history}{all}
```

```
\shufflegroup{all}
```

```
\insertgroup{all}
```

```
\clearpage
```

```
\AMCformBegin
```

This is the answer sheet: all answers are to be ticked on this page to be taken into account.

```
\vspace{2ex}
```

```
\AMCform
```

```
}
```

```
\end{document}
```

First pages of the result are shown on page 9. There are now 2 pages per student: the first with questions, and the second for answers. Only the second will be completed by the students, and scanned for analysis.

2.3 Without markers


With the `nopage` option , package `automultiplechoice` does not include any page markers for scan processing. I'm afraid you can't use any automated marking software with this layout, but you can still use answer sheet and corrected answer sheet (option `indivanswers` , added here) for a manual marking...

The L^AT_EX source `sample-plain.tex` that only differs from `sample-amc.tex` by its options passed to `automultiplechoice`:

```
\usepackage[nopage,indivanswers]{automultiplechoice}
```

produces a 30-pages document, from which we show the first pages on page 10.

First pages from L^AT_EX source detailed in section 2.1 – see sample-amc.pdf

•  • +1/1/50+

AMC SAMPLE TEST

For this test, package `automultiplechoice` is used without any option. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `nowatermark` option.

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1971?

☐ The Soviet Union launches Salyut 1
☐ The first commercial Concorde flight takes off
☐ Death of Louis Armstrong
☐ Apollo 14 lands on the Moon

Question 2 What is the capital of Egypt?

☐ Cayenne
☐ Caracas
☐ Cairo
☐ Conakry
☐ Chisinau


Question 3 Which of the following events are taking place during the year 1850?

☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ First horse-drawn omnibuses established in London
☐ American Express is founded by Henry Wells & William Fargo
☐ Kwang-su becomes emperor of China

Question 4 What is the capital of Ghana?

☐ Accra ☐ Addis Ababa ☐ Ankara ☐ Apia

• For your examination, preferably print documents compiled from `automultiple-choice`. •

•  • +2/1/50+

AMC SAMPLE TEST

For this test, package `automultiplechoice` is used without any option. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `nowatermark` option.

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1901?

☐ The first line of the Paris Metro is opened
☐ Official end of the Crime War of Vietnam
☐ King George of Greece becomes absolute monarch of Crete
☐ Funeral of Queen Victoria in London

Question 2 What is the capital of Ireland?

☐ Djibouti ☐ Dhaka ☐ Doha
☐ Dublin ☐ Dili ☐ Dakar


Question 3 What is the capital of Ghana?

☐ Apia ☐ Accra ☐ Addis Ababa ☐ Ankara

Question 4 Which of the following events are taking place during the year 1850?

☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ First horse-drawn omnibuses established in London
☐ American Express is founded by Henry Wells & William Fargo
☐ Kwang-su becomes emperor of China

• For your examination, preferably print documents compiled from `automultiple-choice`. •

•  • +3/1/50+

AMC SAMPLE TEST

For this test, package `automultiplechoice` is used without any option. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `nowatermark` option.

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1971?

☐ The first commercial Concorde flight takes off
☐ Apollo 14 lands on the Moon
☐ The Soviet Union launches Salyut 1
☐ Death of Louis Armstrong

Question 2 Which of the following events are taking place during the year 1850?

☐ First horse-drawn omnibuses established in London
☐ Kwang-su becomes emperor of China
☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ American Express is founded by Henry Wells & William Fargo


Question 3 What is the capital of Ireland?

☐ Dhaka ☐ Doha ☐ Dakar
☐ Dili ☐ Dublin ☐ Djibouti

Question 4 What is the capital of Thailand?

☐ Beijing ☐ Banja ☐ Bangkok ☐ Beirut ☐ Berlin

• For your examination, preferably print documents compiled from `automultiple-choice`. •

•  • +4/1/50+

AMC SAMPLE TEST

For this test, package `automultiplechoice` is used without any option. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `nowatermark` option.

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1971?

☐ The Soviet Union launches Salyut 1
☐ Apollo 14 lands on the Moon
☐ Death of Louis Armstrong
☐ The first commercial Concorde flight takes off

Question 2 What is the capital of Egypt?

☐ Cayenne
☐ Caracas
☐ Cairo
☐ Conakry
☐ Chisinau

Question 3 Which of the following events are taking place during the year 1850?


☐ American Express is founded by Henry Wells & William Fargo
☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ First horse-drawn omnibuses established in London
☐ Kwang-su becomes emperor of China

Question 4 What is the capital of Ireland?

☐ Djibouti ☐ Dhaka ☐ Dakar
☐ Dili ☐ Doha ☐ Dublin

• For your examination, preferably print documents compiled from `automultiple-choice`. •

First pages from L^AT_EX source detailed in section 2.2 – see sample-separate.pdf



+1/1/60+

AMC

SAMPLE TEST

For this test, package `automultiplechoice` is used with `separatanswersheet` option, so that all answers are to be filled on a separate sheet by students. Page markers are printed in view of an automated marking from papers scans. DLEAPT indications can be cancelled using `nomarkat` option.

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 ▲ Which of the following events are taking place during the year 1971?

- ☐ A The Soviet Union launches Salyut 1
- ☐ B The first commercial Concorde flight takes off
- ☐ C Death of Louis Armstrong
- ☐ D Apollo 14 lands on the Moon

Question 2 What is the capital of Egypt?

- ☐ A Cayenne
- ☐ B Caracas
- ☐ C Cairo
- ☐ D Crenaky
- ☐ E Chisnaun

Question 3 ▲ Which of the following events are taking place during the year 1850?


- ☐ A Napoleon Bonaparte crosses the Alps and invades Italy
- ☐ B First horse-drawn omnibuses established in London
- ☐ C American Express is founded by Henry Wells & William Fargo
- ☐ D Wong-ee becomes Emperor of China

Question 4 What is the capital of Ghana?

- ☐ A Accra
- ☐ B Addis Ababa
- ☐ C Ankara
- ☐ D Apia

For your examination, preferably print documents compiled from `automultiple-choice`.

[illegible][illegible]

•  •

• 2/2/57 •

This is the answer sheet: all answers are to be ticked on this page to be taken into account.

Question 1: ☐ A ☐ B ☐ C ☐ D

Question 2: ☐ A ☐ B ☐ C ☐ D ☐ E

Question 3: ☐ A ☐ B ☐ C ☐ D

Question 4: ☐ A ☐ B ☐ C ☐ D

DRAFT

• For your examination, preferably print documents compiled from auto-multiple-choice. •

First pages from \LaTeX source detailed in section 2.3 – see sample-plain.pdf

AMC

SAMPLE TEST

For this test, package `automultiplechoice` is used with the following options:

- `nosaps`, so that no page markers are printed: nothing is planned for future automated marking from papers scans.
- `indivanswers`, so that correct answers are indicated (this is the corrected answer sheet. Without this option, you get the question sheet).

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 \blacktriangle Which of the following events are taking place during the year 1971?

☒ The Soviet Union launches Salyut 1

☐ The first commercial Concorde flight takes off

☒ Death of Louis Armstrong

☒ Apollo 14 lands on the Moon

Question 2 What is the capital of Egypt?

☐ Cayenne

☐ Caracas

☒ Cairo

☐ Conakry

☐ Chisinau

Question 3 \blacktriangle Which of the following events are taking place during the year 1850?

☐ Napoleon Bonaparte crosses the Alps and invades Italy

☐ First horse-drawn omnibuses established in London

☒ American Express is founded by Henry Wells & William Fargo

☐ Kwang-su becomes emperor of China

Question 4 What is the capital of Ghana?

☒ Accra

☐ Addis Ababa

☐ Ankara

☐ Apia

1

AMC

SAMPLE TEST

For this test, package `automultiplechoice` is used with the following options:

- `nosaps`, so that no page markers are printed: nothing is planned for future automated marking from papers scans.
- `indivanswers`, so that correct answers are indicated (this is the corrected answer sheet. Without this option, you get the question sheet).

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 \blacktriangle Which of the following events are taking place during the year 1901?

☐ The first line of the Paris M tro is opened

☒ Official end of the Caste War of Yucat n

☐ King George of Greece becomes absolute monarch of Crete

☒ Funeral of Queen Victoria in London

Question 2 What is the capital of Ireland?

☐ D ljontzi

☐ Dhaka

☐ Doha

☒ Dublin

☐ D li

☐ D har

Question 3 What is the capital of Ghana?

☐ Apia

☒ Accra

☐ Addis Ababa

☐ Ankara

Question 4 \blacktriangle Which of the following events are taking place during the year 1850?

☐ Napoleon Bonaparte crosses the Alps and invades Italy

☐ First horse-drawn omnibuses established in London

☒ American Express is founded by Henry Wells & William Fargo

☐ Kwang-su becomes emperor of China

1

AMC

SAMPLE TEST

For this test, package `automultiplechoice` is used with the following options:

- `nosaps`, so that no page markers are printed: nothing is planned for future automated marking from papers scans.
- `indivanswers`, so that correct answers are indicated (this is the corrected answer sheet. Without this option, you get the question sheet).

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 \blacktriangle Which of the following events are taking place during the year 1971?

☐ The first commercial Concorde flight takes off

☒ Apollo 14 lands on the Moon

☒ The Soviet Union launches Salyut 1

☒ Death of Louis Armstrong

Question 2 \blacktriangle Which of the following events are taking place during the year 1850?

☐ First horse-drawn omnibuses established in London

☐ Kwang-su becomes emperor of China

☐ Napoleon Bonaparte crosses the Alps and invades Italy

☒ American Express is founded by Henry Wells & William Fargo

Question 3 What is the capital of Ireland?

☐ Dhaka

☐ Doha

☐ Dakar

☐ D li

☒ Dublin

☐ D ljontzi

Question 4 What is the capital of Thailand?

☐ Beijing

☐ Banjul

☒ Bangkok

☐ Beirut

☐ Berlin

1

AMC

SAMPLE TEST

For this test, package `automultiplechoice` is used with the following options:

- `nosaps`, so that no page markers are printed: nothing is planned for future automated marking from papers scans.
- `indivanswers`, so that correct answers are indicated (this is the corrected answer sheet. Without this option, you get the question sheet).

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 \blacktriangle Which of the following events are taking place during the year 1971?

☒ The Soviet Union launches Salyut 1

☒ Apollo 14 lands on the Moon

☒ Death of Louis Armstrong

☐ The first commercial Concorde flight takes off

Question 2 What is the capital of Egypt?

☐ Caracas

☐ Cayenne

☒ Cairo

☐ Conakry

☐ Chisinau

Question 3 \blacktriangle Which of the following events are taking place during the year 1850?

☒ American Express is founded by Henry Wells & William Fargo

☐ Napoleon Bonaparte crosses the Alps and invades Italy

☐ First horse-drawn omnibuses established in London

☐ Kwang-su becomes emperor of China

Question 4 What is the capital of Ireland?

☐ D ljontzi

☐ Dhaka

☐ Doha

☐ Dublin

☐ D li

☒ Dublin

1

3 Usage

3.1 Package options

The following options are available for package `automultiplechoice`:

`noshuffle` cancels answers shuffling for all questions.

`answers` produces a common corrected answers sheet.

`indivanswers` shows the boxes that corresponds to correct choices on the question sheet.

`box` includes every question in a \LaTeX box, so that they can't be cutted on two different pages.

`separateanswersheet` asks for a separate answer sheet (see section 2.2 for an example). Commands `\AMCformBegin` and `\AMCform` must be used to describe the separate answer sheet (see section 3.6).

`digits` puts digits instead of letters in the boxes, when `separateanswersheet` (or `insidebox`) is used.

`outsidebox` prints boxes labels outside the boxes on the answersheet when `separateanswersheet` is set.

`init` initializes the random generator from time. *This option is only for testing: don't use it for a real exam!*

`completemulti` adds an answer "None of these answers are correct." at the end of each multiple question (question with no, one or several correct answers), so as to make the difference between "I don't know" and "I think none of the answers are correct".

`insidebox` puts a letter (or a digit if `digits` option is used) inside the boxes, even if `separateanswersheet` is not used. The `insidebox` option is implicitly called when using `separateanswersheet`: no need to call it then.

`calibration` asks for logging positions of boxes and markers in the `.xy` file. Without this option, a \LaTeX run updates the document but not the `.xy` file.

`nowatermark` cancels the "DRAFT" indications above pages.

`catalog` is used for formatting a catalog of questions, not an exam. Then the questions identifiers will be printed.

`francais` asks for french localisation.

`lang=XX` asks for localisation in `XX` language. At present, only `FR` (french) and `ES` (spanish) are available.

`plain` cancels `environ` and `etex` automatic loading. The default behaviour is to load `environ` and `etex` packages if available, as they improve `automultiplechoice`. This is not done when `plain` option is set.

`nopage` cancels markers print and page layout definition (see sample in section 2.3).

`postcorrect` tells that correct answers won't be given in the \LaTeX source. The teacher will fill one answer sheet for AMC to analyse the scan and set correct answers from it.

See also section 3.8 for a french version of some of these options.

3.2 Questions and answers

We make a difference between two kind of multiple choice questions:

- **Simple questions:** there is one and only one correct choices among the proposed choices, *and this is announced to the student*. Thus, the student is asked to check one answer if he thinks this is the good one, and to check none if he has no idea.
- **Multiple questions:** there can be zero, one or several correct choices among the proposed choices. This is also announced to the student (using the `\multiSymbole` sign, with default ♣), so that the student is asked to check all the boxes corresponding to correct choices, and to let unchecked all boxes corresponding to wrong choices.

`question`
`questionmult`

Simple questions are enclosed in a `{question}{⟨id⟩}` environment, and multiple questions are enclosed in a `{questionmult}{⟨id⟩}` environment. These environments contain the question text, and the proposed choices inside a `choices`-like environment (see next). The `⟨id⟩` argument is a question identifier. Each question must have a unique identifier, different from the other questions identifiers.

`choices`
`choiceshoriz`
`choicescustom`

Depending on the formatting style for answers, one can choose one of the following ones:

- Environment `choices` is usually chosen for long answers:

```
\begin{questionmult}{latex}
  What are the possible uses of latex?
  \begin{choices}
    \correctchoice{Natural rubber is
      the most important product
      obtained from latex.}
    \correctchoice{Latex from the chicle
      and jelutong trees is used in
      chewing gum.}
    \wrongchoice{Latex is used as a fuel
      for some space launch vehicles.}
  \end{choices}
\end{questionmult}
```

Question 1 ♣ What are the possible uses of latex?

- ☐ Latex from the chicle and jelutong trees is used in chewing gum.
- ☐ Latex is used as a fuel for some space launch vehicles.
- ☐ Natural rubber is the most important product obtained from latex.

- environment `choiceshoriz` is chosen for short answers:

```
\begin{question}{insect}
  From those animals, which
  is an insect?
  \begin{choiceshoriz}
    \correctchoice{Ant}
    \wrongchoice{Horse}
    \wrongchoice{Turtle}
  \end{choiceshoriz}
\end{question}
```

Question 1 From those animals, which is an insect?

- ☐ Horse ☐ Turtle ☐ Ant

- environment `choicescustom` is provided to customize answers formatting. See 3.9.3 for details.

`\correctchoice` As you have seen in these examples, the `choices`-like environments contain `\correctchoice{<text>}` and `\wrongchoice{<text>}` commands, with the text of the proposed choice as argument.

3.3 Scoring

`\scoring` Scoring strategies can be given in the L^AT_EX source. They don't have any impact on the question sheet: they are only transmitted to the analysis software through the `.amc` file. See AMC documentation to write proper commands for your needs. `\scoring{<score>}` can be used inside a question or `questionmult` environment to describe the scoring strategy for the question, or after a `\correctchoice` or `\wrongchoice` command to describe score associated to a particular choice. `\scoringDefaultM{<score>}` and `\scoringDefaultS{<score>}` define default scoring strategies for multiple and simple questions. `\QuestionIndicative` tags a question that is not taken into account to compute the mark – for example, it can be used for a question about the way students have enjoyed the course.

3.4 Groups of questions

Several commands are available that allows shuffling questions for each question sheet. They handle groups of questions. These groups will usually contain questions, but can be made of any L^AT_EX content.

`\element` The command `\element{<groupname>}{<content>}` adds element with content `<content>` to the group named `<groupname>`. The command `\shufflegroup{<groupname>}` shuffles elements of group named `<groupname>`. The command `\insertgroup[<n>]{<groupname>}` inserts elements of group `<groupname>` one after one. If optional parameter `<n>` is given, only the first `<n>` elements of the group are inserted in the document.

As an example without questions in groups elements, consider the following code:

```
\element{serie}{ one}
\element{serie}{ two}
\element{serie}{ three}
\element{serie}{ four}
\element{serie}{ five}
Numbers:\insertgroup{serie}.

\shufflegroup{serie}
Two of them:\insertgroup[2]{serie}.
```

which produces:

Numbers: one two three four five. Two of them: two four.

`\cleargroup` The command `\cleargroup{<groupname>}` clears all the elements of group `<groupname>`, making an empty group. The command `\copygroup[<n>]{<from>}{<to>}` copies the elements of group `<from>` to group `<to>` – if optional parameter `<n>` is given, only the `<n>` first elements are copied.

As an example again without questions, consider the following code:

```

\element{digits}{ 1}\element{digits}{ 2}\element{digits}{ 3}
\element{digits}{ 4}\element{digits}{ 5}\element{digits}{ 6}
\element{digits}{ 7}\element{digits}{ 8}\element{digits}{ 9}
\element{letters}{ A}\element{letters}{ B}\element{letters}{ C}
\element{letters}{ D}\element{letters}{ E}\element{letters}{ F}

```

```

\shufflegroup{digits}\shufflegroup{letters}
\cleargroup{mixed}
\copygroup[3]{digits}{mixed}\copygroup[2]{letters}{mixed}
\shufflegroup{mixed}
Three digits and two letters:\insertgroup{mixed}.

```

```

\shufflegroup{digits}\shufflegroup{letters}
\cleargroup{mixed}
\copygroup[3]{digits}{mixed}\copygroup[2]{letters}{mixed}
\shufflegroup{mixed}
Three digits and two letters:\insertgroup{mixed}.

```

which produces:

Three digits and two letters: E 7 5 C 9.
Three digits and two letters: 8 6 A C 4.

You can find an example involving questions in section 2.

3.5 Students identification

`\namefield` There are two ways to associate students to their sheets.

`\AMCcode`
`\AMCcodeH`

- Always add to one page of each copy some place for the student to write down his name. If you want AMC software to be able to cut the scan around this area to present it to you and ask you to read the written name (this is called manual association), you must use the `\namefield{<descr>}` command. The `<descr>` argument contains the \LaTeX code used to format the name field on the page. For example:

```

\namefield{\fbox{
  \begin{minipage}{15em}
    Name and surname:\vspace*{3ex}\par
    \noindent\dotfill\vspace{2mm}
  \end{minipage}
}}

```

Name and surname:

.....

You can see that the `\namefield` command has no effect on the produced document. In fact, its only purpose is to log in the `.xy` file information about the position of the name field on the page, to be used by the software analysing the scans.

- For automated student identification, if for example students have a 6-digits student number, you can ask them to code it somewhere on the question sheet. This can be done using the `\AMCcode{<key>}{<ndigits>}` command, where `<key>` is the key identifier, that can be used

to retrieve coded student numbers from the scans, and $\langle ndigits \rangle$ is the number of digits for numbers to be coded.

`\AMCcode{student}{6}`

<input type="text"/>	0	<input type="text"/>	0	<input type="text"/>	0	<input type="text"/>	0	<input type="text"/>	0	<input type="text"/>	0
<input type="text"/>	1	<input type="text"/>	1	<input type="text"/>	1	<input type="text"/>	1	<input type="text"/>	1	<input type="text"/>	1
<input type="text"/>	2	<input type="text"/>	2	<input type="text"/>	2	<input type="text"/>	2	<input type="text"/>	2	<input type="text"/>	2
<input type="text"/>	3	<input type="text"/>	3	<input type="text"/>	3	<input type="text"/>	3	<input type="text"/>	3	<input type="text"/>	3
<input type="text"/>	4	<input type="text"/>	4	<input type="text"/>	4	<input type="text"/>	4	<input type="text"/>	4	<input type="text"/>	4
<input type="text"/>	5	<input type="text"/>	5	<input type="text"/>	5	<input type="text"/>	5	<input type="text"/>	5	<input type="text"/>	5
<input type="text"/>	6	<input type="text"/>	6	<input type="text"/>	6	<input type="text"/>	6	<input type="text"/>	6	<input type="text"/>	6
<input type="text"/>	7	<input type="text"/>	7	<input type="text"/>	7	<input type="text"/>	7	<input type="text"/>	7	<input type="text"/>	7
<input type="text"/>	8	<input type="text"/>	8	<input type="text"/>	8	<input type="text"/>	8	<input type="text"/>	8	<input type="text"/>	8
<input type="text"/>	9	<input type="text"/>	9	<input type="text"/>	9	<input type="text"/>	9	<input type="text"/>	9	<input type="text"/>	9

For smaller number of digits, the “horizontal” form can be preferred:

`\AMCcodeH{student}{3}`

<input type="text"/>	0	<input type="text"/>	1	<input type="text"/>	2	<input type="text"/>	3	<input type="text"/>	4	<input type="text"/>	5	<input type="text"/>	6	<input type="text"/>	7	<input type="text"/>	8	<input type="text"/>	9
<input type="text"/>	0	<input type="text"/>	1	<input type="text"/>	2	<input type="text"/>	3	<input type="text"/>	4	<input type="text"/>	5	<input type="text"/>	6	<input type="text"/>	7	<input type="text"/>	8	<input type="text"/>	9
<input type="text"/>	0	<input type="text"/>	1	<input type="text"/>	2	<input type="text"/>	3	<input type="text"/>	4	<input type="text"/>	5	<input type="text"/>	6	<input type="text"/>	7	<input type="text"/>	8	<input type="text"/>	9

3.6 Separate answer sheet

`\AMCformBegin`
`\AMCform`
`\MCcleardoublepage`

To produce separate answer sheets as seen in section 2.2,

1. use the `separateanswersheet` package option.
2. use the `\AMCformBegin` command at the beginning of the answer sheet description. This command usually follows a command to get a new page. This command can be the classical `\clearpage` for single-sided question sheets, or the `\AMCcleardoublepage` command, that go to the next odd numbered page, so that the answer sheet is on a separate sheet even when printing in duplex mode.
3. use the `\AMCform` command to insert all boxes for all questions.

See section 2.2 for an example.

3.7 Random computation questions

One can use the \LaTeX package `fp` to make random computation questions, as can be seen in the following example (don’t forget to load package `fp`):

`\begin{question}{simpler}`

`\FPeval\VQa{trunc(1+random*8,0)}`

`\FPeval\VQb{trunc(4+random*5,0)}`

`\FPeval\VQsum{clip(VQa+VQb)}`

`\FPeval\VQnoA{clip(VQa+VQb-1)}`

`\FPeval\VQnoB{clip(VQa*VQb)}`

Question 1

How much are 2 plus 8?

<input type="text"/>	9	<input checked="" type="checkbox"/>	10	<input type="text"/>	-6	<input type="text"/>	16
----------------------	---	-------------------------------------	----	----------------------	----	----------------------	----

```

\FPeval\VQnC{clip(VQa-VQb)}
How much are \VQa{} plus \VQb{}?
\begin{choiceshoriz}
  \correctchoice{\VQsum}
  \wrongchoice{\VQnoA}
  \wrongchoice{\VQnoB}
  \wrongchoice{\VQnoC}
\end{choiceshoriz}
\end{question}

```

In this example, `\VQa` and `\VQb` are used to store two random integers (the first between 1 and 8, and the second between 4 and 8). Then `\VQsum` stores the sum of these two integers, and `\VQnoA`, `\VQnoB` and `\VQnoC` are other values that will be used as distractors in the multiple choice question.

`\AMCIntervals` In some cases, command `\AMCIntervals{⟨x⟩}{⟨x0⟩}{⟨x1⟩}{⟨delta⟩}` from `automultiplechoice` can be usefull. It adds a sequence of choices made of intervals $[x_i, x_i + \delta[$ of length $\langle delta \rangle$ covering the interval $[\langle x0 \rangle, \langle x1 \rangle[$, using `\correctchoice` when $\langle x \rangle$ lies in the interval, and `\wrongchoice` otherwise.

```

\begin{question}{inf-expo-indep}
\FPeval\VQa{trunc(2 + random * 4,0)}
\FPeval\VQb{trunc(6 + random * 5,0)}
\FPeval\VQr{VQa/(VQa+VQb)}
Let  $\$X\$$  and  $\$Y\$$  be two independent random variables, following
exponential laws with respective parameters  $\VQa{}$  and  $\VQb{}$ .
In which interval lies the probability  $\$\text{trm}{P}[X<Y]\$$ ?
\begin{multicols}{5}
  \begin{reponses}[o]
    \AMCIntervals{\VQr}{0}{1}{0.1}
  \end{reponses}
\end{multicols}
\end{question}

```

Question 1

Let X and Y be two independent random variables, following exponential laws with respective parameters 5 and 8. In which interval lies the probability $P[X < Y]$?

- | | | | | |
|---------------------------------------|--|---------------------------------------|---------------------------------------|---------------------------------------|
| <input type="checkbox"/> $[0, 0.1[$ | <input type="checkbox"/> $[0.2, 0.3[$ | <input type="checkbox"/> $[0.4, 0.5[$ | <input type="checkbox"/> $[0.6, 0.7[$ | <input type="checkbox"/> $[0.8, 0.9[$ |
| <input type="checkbox"/> $[0.1, 0.2[$ | <input checked="" type="checkbox"/> $[0.3, 0.4[$ | <input type="checkbox"/> $[0.5, 0.6[$ | <input type="checkbox"/> $[0.7, 0.8[$ | <input type="checkbox"/> $[0.9, 1[$ |

3.8 French command names

For backward compatibility, some of `automultiplechoice` commands, environments and package option have their French counterpart. You can always use either the English command or the French equivalent. See table 1 for details.

type	English	French
command	<code>\namefield</code>	<code>\champnom</code>
environment	<code>choices</code>	<code>reponses</code>
environment	<code>choiceshoriz</code>	<code>reponseshoriz</code>
environment	<code>choicescustom</code>	<code>reponsesperso</code>
command	<code>\correctchoice</code>	<code>\bonne</code>
command	<code>\wrongchoice</code>	<code>\mauvaise</code>
command	<code>\lastchoices</code>	<code>\alafin</code>
command	<code>\AMCIntervals</code>	<code>\choixIntervalles</code>
command	<code>\scoring</code>	<code>\bareme</code>
command	<code>\scoringDefaultM</code>	<code>\baremeDefautM</code>
command	<code>\scoringDefaultS</code>	<code>\baremeDefautS</code>
command	<code>\onecopy</code>	<code>\exemplaire</code>
environment	<code>examcopy</code>	<code>copieexamen</code>
command	<code>\shufflegroup</code>	<code>\melangegroupe</code>
command	<code>\insertgroup</code>	<code>\restituegroupe</code>
command	<code>\AMCform</code>	<code>\formulaire</code>
command	<code>\AMCformBegin</code>	<code>\AMCdebutFormulaire</code>
option	<code>noshuffle</code>	<code>ordre</code>
option	<code>answers</code>	<code>correc</code>
option	<code>indivanswers</code>	<code>correcindiv</code>
option	<code>box</code>	<code>bloc</code>
option	<code>separateanswersheet</code>	<code>ensemble</code>
option	<code>digits</code>	<code>chiffres</code>

Table 1: French equivalent commands

3.9 Customisation

3.9.1 Boxes

`\AMCboxDimensions` The command `\AMCboxDimensions{⟨dims⟩}` can be used to specify the dimensions of the boxes to be ticked. The argument `⟨dims⟩` is a coma-separated list of `⟨key⟩=⟨value⟩` pairs, with the following possible `⟨key⟩`s:

`size` for the size of the edges of the boxes.

`down` for the length the boxes are to be moved down.

`rule` for the rule width.

Default values are `\AMCboxDimensions{size=2.5ex,down=.4ex,rule=.5pt}`

3.9.2 Codes

One may adapt the codes rendering from `\AMCcode` to one's needs modifying the following lengths:

- `\AMCcodeHspace` is the amount of horizontal space between two columns of digits,

- `\AMCcodeHspace` is the amount of vertical space between two rows of digits,
- `\AMCcodeBoxSep` is the amount of space between the box and the label, when the label is printed outside the box.

Default values are `\AMCcodeHspace=.5em \AMCcodeVspace=.5em \AMCcodeBoxSep=.1em`

3.9.3 Answers

Environment `choicescustom` will make use of the three commands `\AMCbeginAnswer` (before the first answer), `\AMCendAnswer` (after the last answer) and `\AMCanswer{<box>}{<text>}` (for each answer) to format the answers. Redefining them properly, some different answers formatting can be achieved. However, this does not seem to work with non-trivial settings...

```
\begin{question}{add}
  \def\AMCbeginAnswer{$\Big($}
  \def\AMCendAnswer{$\Big)$}
  \def\AMCanswer#1#2{#1 #2\hfill}
  2+2=
  \begin{choicescustom}
    \correctchoice{4}
    \wrongchoice{2}
    \wrongchoice{3}
  \end{choicescustom}
\end{question}
```

| Question 1 2+2= (☐ 4 ☐ 3 ☐ 2)

4 Implementation

This package uses the following other packages:

```
1 \RequirePackage{xcolor} % \fcolorbox to fill (or not) a box
2 \RequirePackage{fancyhdr} % \pagestyle{empty}
3 \RequirePackage{bophook} % \AtBeginPage
4 \RequirePackage{xkeyval} % \setkeys
5 \RequirePackage{rotating} % \rotatebox
```

It defines a version string:

```
6 \def\AMC@VERSION{AMC 1.0.3 svn:704 with style $Revision: 431 $}
```

`\AMC@amclog` Informations about questions and choices will be logged to a file with extension `amc`, to be parsed later. Macro `\AMC@amclog` writes to this file.

```
7 \newwrite\AMC@logfile
8 \immediate\openout\AMC@logfile=\jobname.amc
9 \def\AMC@amclog#1{\immediate\write\AMC@logfile{#1}}
10 \def\AMCmessage#1{\AMC@amclog{AUTOQCM[#1]^^J}}
```

`\AMC@LR` Colours management can be faulty in right-to-left mode: in these situations, we will make use of `\LR` from package `bidi` to get back to left-to-right mode. `\AMC@LR` is `\LR` if `bidi` is loaded.

```
11 \AtBeginDocument{\@ifpackageloaded{bidi}{%
12   \PackageInfo{automultiplechoice}{Package bidi loaded: using LR for boxes.}}%
```

```

13 \let\AMC@LR=\LR}%
14 {\let\AMC@LR=\relax}}%

```

4.1 Variables

Counters and boolean variables defined here are internal and should not be modified by the user.

The package defines the following counters:

`\AMCload@counter` number of choices already loaded for current question.

`\AMCid@quest` current question ID number (see section 4.5).

`\AMCid@etud` current student sheet number.

`\AMCid@check` current page checking number.

`\AMCid@etudfin` last student sheet number for the exam.

`\AMCnum@copies` number of exam sheets to produce.

It also defines the following switches:

`\ifAMC@ordre` if choices are never to be shuffled.

`\ifAMC@correthead` if some correction header is to be printed at the beginning.

`\ifAMC@affichekeys` if questions keys are to be printed.

`\ifAMC@correc` if correct choices are to be checked on the produced document.

`\ifAMC@qbloc` if questions are to be included in \LaTeX boxes (so that they can't be splitted on two different pages).

`\ifAMC@rbloc` if answers are to be included in \LaTeX boxes (so that they can't be splitted on two different columns for example).

`\ifAMCcomplete@multi` if a choice "None of these answers are correct." is to be added to every multiple question.

`\ifAMC@calibration` if this \LaTeX run is used to get page layouts.

`\ifAMC@plain` if `automultiplechoice` won't try to load usefull packages (`etex`, `environ`) that extend `automultiplechoice` capabilities.

`\ifAMCune@bonne` if there is at least one correct answer for the current question.

`\ifAMCtype@multi` if the current question is a multiple question.

`\ifAMC@watermark` if the document is a draft, not to be used for exam.

`\ifAMC@ensemble` if answers are to be given on a separate answers sheet.

`\ifAMC@inside@box` if a letter or digit is to be printed inside all boxes.

`\ifAMC@inside@digit` if digits are to be written inside boxes instead of letters (when using a separate answer sheet for example).

`\ifAMC@outside@box` if labels for boxes are to be printed outside the box on the answer sheet.

`\ifAMCformulaire@dedans` is true for questions inside separate answer sheet.

`\ifAMC@zoneformulaire` is true for codes (made by `\AMCcode`) inside separate answer sheet.

`\ifAMC@pagelayout` is true if the AMC page layout, with signs for scan analysis, is to be used.

`\ifAMC@postcorrect` corresponds to the use of the `postcorrect` package option.

```

15 \newcount\AMCload@counter
16 \newcount\AMCid@quest\AMCid@quest=-1
17 \newcount\AMCid@check
18 \newcount\AMCid@etud\AMCid@etud=0
19 \newcount\AMCid@etudfin
20 \newcount\AMCnum@copies

21 \newif\ifAMC@ordre\AMC@ordrefalse
22 \newif\ifAMC@correthead\AMC@corretheadfalse
23 \newif\ifAMC@affichekeys\AMC@affichekeysfalse
24 \newif\ifAMC@correc\AMC@correcfalse
25 \newif\ifAMC@qbloc\AMC@qblocfalse
26 \newif\ifAMC@rbloc\AMC@rblocfalse
27 \newif\ifAMC@complete@multi\AMC@complete@multifalse
28 \newif\ifAMC@calibration\AMC@calibrationfalse
29 \newif\ifAMC@plain\AMC@plainfalse
30 \newif\ifAMC@bonne
31 \newif\ifAMC@type@multi
32 \newif\ifAMC@watermark\AMC@watermarktrue
33 \newif\ifAMC@inside@box\AMC@inside@boxfalse
34 \newif\ifAMC@outside@box\AMC@outside@boxfalse
35 \newif\ifAMC@ensemble\AMC@ensemblefalse
36 \newif\ifAMC@inside@digit\AMC@inside@digitfalse
37 \newif\ifAMCformulaire@dedans\AMCformulaire@dedansfalse
38 \newif\ifAMC@zoneformulaire
39 \newif\ifAMC@pagelayout\AMC@pagelayouttrue
40 \newif\ifAMC@postcorrect\AMC@postcorrectfalse

```

`\AMCid@name` The package also defines command `\AMCid@name` to be the current question identifier key.

```
41 \def\AMCid@name{}
```

4.2 Dimensions

`\AMCformVSpace` The following dimensions can be modified by the user to adjust questions formatting:

`\AMCformHSpace` `\AMCformVSpace` is the amount of vertical space between two questions in a separate answer sheet.

`\AMCinterIrep` `\AMCformHSpace` is the amount of horizontal space between two answers boxes in a separate answer sheet.

`\AMCinterBrep`

`\AMCinterIrep` is the amount of vertical space to be added between two answers.

`\AMCinterBrep` is the amount of vertical space between two boxed answers (see `\AMCBoxedAnswers` and `\ifAMC@rbloc`).

```
42 \newdimen\AMCformVSpace\AMCformVSpace=1.2ex
43 \newdimen\AMCformHSpace\AMCformHSpace=.3em
44 \newdimen\AMCinterIrep\AMCinterIrep=\z@
45 \newdimen\AMCinterBrep\AMCinterBrep=.5ex
```

4.3 Localisation

In this section, some localised strings or commands are defined, for English, French and Spanish languages.

`\AMCtext` To modify these texts, you can use command `\AMCtext`. For example, `\AMCtext{draft}{\langle text \rangle}` sets the text to be printed behind each page of a draft exam.

```
46 \def\AMCtext#1#2{\expandafter\def\csname AMC@loc@#1\endcsname{#2}}
```

4.3.1 English

Text indicating draft exams:

```
47 \def\AMC@loc@draft{DRAFT}
```

Message at page bottom when compiled out of AMC gui:

```
48 \def\AMC@loc@message{For your examination, preferably print
49 documents compiled from auto-multiple-choice.}
```

Announcing a question in a separate sheet (parameter #1 is the question number):

```
50 \def\AMC@loc@qf#1{\textbf{Question #1:}}
```

Announcing a question (parameter #1 is the question number and parameter #2 can be the multiple question symbol, or be empty):

```
51 \def\AMC@loc@q#1#2{\textbf{Question #1} #2}
```

Headers for corrected version and catalog:

```
52 \def\AMC@loc@corrected{Corrected}
53 \def\AMC@loc@catalog{Catalog}
```

Last choice added at the end for multiple questions when option `completemulti` is used:

```
54 \def\AMC@loc@none{None of these answers are correct.}
```

4.3.2 French

French localisation is called with option `francais`.

```
55 \def\AMC@loc@FR{
56   \def\AMC@loc@draft{PROJET}
57   \def\AMC@loc@message{Pour votre examen, imprimez de pr\'eference
58     les documents compil\'es \'a l'aide de auto-multiple-choice.}
59   \def\AMC@loc@qf##1{\textbf{Question ##1 :}}
60   \def\AMC@loc@q##1##2{\textbf{Question ##1} ##2}
61   \def\AMC@loc@corrected{Correction}
```

```

62 \def\AMC@loc@catalog{Catalogue}
63 \def\AMC@loc@none{Aucune de ces r\'eponses n'est correcte.}
64 }

```

4.3.3 Spanish

4.3.4 Other languages

Other languages can be integrated to automultiplechoice package upon request to the author.

4.4 Random

4.4.1 Random pseudo-generator

The package uses the pseudo-random bit generator from *TuGBoat* 1994, vol 15:1:

```

65 \ifx\AMC@SR\undefined\newcount\AMC@SR\fi
66 \providecommand\AMC@SRconst{2097152}
67 \providecommand\AMC@SRset[1]{\global\AMC@SR#1 \ignorespaces}
68 \providecommand\AMC@SRadvance{%
69   \begingroup%
70     \ifnum\AMC@SR<\AMC@SRconst\relax\AMC@SR@count\z@else\AMC@SR@count\@ne\fi%
71     \ifodd\AMC@SR\advance\AMC@SR@count\@ne\fi%
72     \global\divide\AMC@SR\tw@%
73     \ifodd\AMC@SR@count\global\advance\AMC@SR\AMC@SRconst\relax\fi%
74   \endgroup}
75 \providecommand\AMC@SRbit{\AMC@SRadvance\ifodd\AMC@SR1\else0\fi}
76 \providecommand\AMC@SRtest[2]{\AMC@SRadvance%
77   \ifodd\AMC@SR#2\else#1\fi\ignorespaces}
78 \providecommand\AMC@SRvalue{\number\AMC@SR}

```

`\AMCrandomseed` The seed of this generator is set to 1515, but another value can be given using the command `\AMCrandomseed{<seed>}`.

```

79 \AMC@SRset{1515}
80 \def\AMCrandomseed#1{\AMC@SRset{#1}}

```

4.4.2 Uniform random deviates

`\AMC@SRnextByte` This generator is used to build first a 20-bit uniform integer generator (macro `\AMC@SRnextByte`).
`\AMC@SRmax` Then, using modulo, a (nearly) uniform generator on $\{0, \dots, n-1\}$ is built: command `\AMC@SRmax{n}` puts in `\AMC@SR@count` the random deviate.

```

81 \newcount\AMC@SR@count
82 \def\AMC@SR@time{\AMC@SRset{\time}}
83 \newcount\AMC@SRnum
84 \def\AMC@SRnextByte{\AMC@SRnum=\z@%
85   \AMC@SR@count=20%
86   \loop\multiply\AMC@SRnum\tw@%
87     \AMC@SRtest{\advance\AMC@SRnum\@ne}{}%
88   \ifnum\AMC@SR@count>\@ne\advance\AMC@SR@count\m@ne\repeat%
89 }
90 \newcommand\AMC@SRmax[1]{\AMC@SRnextByte%

```

```

91 \AMC@SR@count=\AMC@SRnum%
92 \divide\AMC@SR@count by #1\relax%
93 \multiply\AMC@SR@count by #1\relax%
94 \advance\AMC@SRnum by -\AMC@SR@count%
95 }

```

4.4.3 Tokens shuffling

`\AMCsw@p` The package defines the macro `\AMCsw@p` to swap the values of two token registers given as parameters.

After defining n token registers `\foo@i`, `\foo@ii`, `\foo@iii`, `\foo@iv` and so on, you can shuffle them using `\AMC@shuffletoks{n}{foo@}`.

```

96 \newcount\AMC@sti
97 \newtoks\AMCsw@p@
98 \newcommand\AMCsw@p[2]{%
99   \global\AMCsw@p@=#1%
100   \global#1=#2%
101   \global#2=\AMCsw@p@}
102 \newcommand\AMC@shuffletoks[2]{%
103   \AMC@sti=#1\relax%
104   \@whilenum\AMC@sti>\@ne\do{%
105     \AMC@SRmax{\AMC@sti}\advance\AMC@SRnum\@ne\relax%
106     \AMCsw@p{\csname #2\romannumeral\AMC@SRnum\endcsname}%
107       {\csname #2\romannumeral\AMC@sti\endcsname}%
108     \advance\AMC@sti\m@ne\relax%
109   }}

```

4.5 Keys numbering

`\AMC@unnumero` This package allocates a unique integer ID to each question key from the questionnaire. The counter `\AMC@numerotation` keeps track of the number of keys which already had an ID. Command `\AMC@definitnumero{n}{key}` allocates ID n to the key `key`. Command `\AMC@prepare{key}` looks if an ID had already been associated to `key`, and, if not, makes a new ID allocation for `key`. Command `\AMC@unnumero{key}` returns the ID associated with `key` (creating one if necessary). Command `\AMC@affecte{key}{\cnt}` give to counter `\cnt` the value of the ID associated to `key` (creating one if necessary).

```

110 \newcount\AMC@numerotation\AMC@numerotation=\z@%
111 \def\AMC@definitnumero#1#2{\AMC@amclog{AUTOQCM[ NUM=#1=#2]^^J}%
112   \expandafter\global\expandafter\def\csname AMC@numtab@#2\endcsname{#1}}
113 \def\AMC@prepare#1{\expandafter\ifx\csname AMC@numtab@#1\endcsname\relax%
114   \global\advance\AMC@numerotation\@ne%
115   \expandafter\AMC@definitnumero\expandafter{\the\AMC@numerotation}{#1}\fi}
116 \def\AMC@unnumero#1{\AMC@prepare{#1}\csname AMC@numtab@#1\endcsname}
117 \def\AMC@affecte#1#2{\AMC@prepare{#1}#2=\csname AMC@numtab@#1\endcsname}

```

4.6 Boxes

4.6.1 Position logging

`\AMC@tracebox` Command `\AMC@tracebox{<trace>}{<key>}{<content>}` makes a L^AT_EX box around `<content>`, and, if `<trace>` is not empty, logs to the `.xy` file informations to be able to compute exact location of this box on the page, attached to the box identification `<key>`.

Command `\AMC@pagepos` logs page and page size informations at the beginning of each page.

```

118 \def\AMC@tracepos#1#2{%
119   \ifAMC@calibration\ifx\@empty#1\@empty\else%
120     \pdfsavepos\protected@write\AMC@XYFILE{}{%
121       \string\tracepos%
122       {\the\AMCid@etud/\thepage:#2}%
123       {\noexpand\number\pdflastxpos sp}%
124       {\noexpand\number\pdflastypos sp}}%
125   \fi\fi}
126 \def\AMC@traceposx#1#2{%
127   \ifAMC@calibration\ifx\@empty#1\@empty\else%
128     \pdfsavepos\protected@write\AMC@XYFILE{}{%
129       \string\tracepos%
130       {\the\AMCid@etud/\thepage:#2}%
131       {\noexpand\number\pdflastxpos sp}%
132       {0sp}}%
133   \fi\fi}
134 \def\AMC@traceposy#1#2{%
135   \ifAMC@calibration\ifx\@empty#1\@empty\else%
136     \pdfsavepos\protected@write\AMC@XYFILE{}{%
137       \string\tracepos%
138       {\the\AMCid@etud/\thepage:#2}%
139       {0sp}%
140       {\noexpand\number\pdflastypos sp}}%
141   \fi\fi}
142 \newcommand\AMC@tracebox[3]{%
143   \vbox{\AMC@traceposy{#1}{#2}%
144     \hbox{\AMC@traceposx{#1}{#2}\AMC@traceposx{#1}{#2}}%
145     \AMC@traceposy{#1}{#2}}
146 \def\AMC@pagepos{%
147   \ifAMC@calibration\protected@write\AMC@XYFILE{}{%
148     \string\page%
149     {\the\AMCid@etud/\thepage/\the\AMCid@check}%
150     {\the\paperwidth}{\the\paperheight}}\fi}

```

`amcxyfile` The following lines defines an environment to use a particular file for positions outputs. This is used mainly for documentation or testing.

```

151 \newwrite\AMC@XYspecial
152 \newwrite\AMC@tmpXY
153 \newenvironment{amcxyfile}[1]{%
154   \openout\AMC@XYspecial#1%
155   \let\AMC@tmpXY=\AMC@XYFILE%
156   \let\AMC@XYFILE=\AMC@XYspecial%

```



```
157 }\let\AMC@XYFILE=\AMC@tmpXY\closeout\AMC@XYSpecial}
```

`\namefield` The `\namefield{<name field content>}` is a simple call to `\AMC@tracebox`:

```
158 \newcommand{\namefield}[1]{\AMC@tracebox{1}{nom}{#1}}
```

It is used to enclose the page region where students are to write their names, so as to retrieve it easily from the scans. For example,

```
\namefield{\fbox{%
  \begin{minipage}{5cm}
    Name:

    \vspace*{.5cm}\noindent\dotfill
    \vspace{2mm}
  \end{minipage}}}
```

produces the following box:

Name:

and outputs information about the position of the box in the `.xy` file, as seen in section 5.1.

4.6.2 Boxes to be checked by students

`\AMC@boxedchar` There are two styles for boxes to be checked by the students. The first one is an empty box, printed beside the answer. The second is a box with a character in it. It is mainly used when answers are to be given on a separate answer sheet.

These boxes can be drawn using command `\AMC@boxedchar{<char>}{<trace>}{<key>}{<filled>}`: `<char>` is the character to print inside the box, `<trace>` is non-empty if you want to log the box position in the `.xy` file, `<key>` is the box identification, and `<filled>` is non-empty for filling the box.

For example, `\AMC@boxedchar{K}{1}{test}{}` produce the box

K

, writing the lines in the `.xy` file shown in section 5.2.

```
159 \newcommand\AMC@boxedchar[4]{\AMC@LR{\hspace{0pt}%
160   {\fboxsep=\z@\fboxrule=\AMC@boxedrule%
161     \lower\AMC@boxeddown\hbox{\fcolorbox{black}%
162       {\ifx\@empty#4\@empty white\else black\fi}%
163       {\vbox to \AMC@boxeddim{\AMC@tracepos{#2}{#3}\vfill %
164         \hbox to \AMC@boxeddim{\hfill{#1}\hfill}\vfill}%
165       \AMC@tracepos{#2}{#3}}}}}
```

`\AMC@caselettre` Command `\AMC@caselettre` is the same as `\AMC@boxedchar`, but if `<char>` is empty, it is replaced by an arabic or alphabetical counter, depending on the use of the `digits` package option.

`\AMCchoiceLabel`

To use another way to label the choices boxes, the user can redefine the `\AMCchoiceLabel` macro, which takes as argument the name of the counter used to number the choices. One can for example use `\def\AMCchoiceLabel#1{\alph{#1}}` to ask for lowercase letters.

```

166 \def\AMCchoiceLabel#1{%
167   \ifAMC@inside@digit\arabic{#1}%
168   \else\Alph{#1}\fi%
169 }
170 \newcounter{AMC@ncase}
171 \setcounter{AMC@ncase}{0}
172 \newcommand\AMC@caselettre[4]{%
173   \AMC@boxedchar{\ifx\@empty#1\@empty%
174     \AMCchoiceLabel{AMC@ncase}%
175     \else #1\fi}{#2}{#3}{#4}}

```

\AMCboxDimensions The dimensions of these box are managed by `\AMCboxDimensions{<sizes>}`, where `<sizes>` is a coma separated list of `<name>=<dimension>` constructs. Here, `<name>` can be **size** for the box size, **rule** for the box rule width and **down** for moving the box down.

```

176 \newlength\AMC@boxedrule
177 \newlength\AMC@boxeddown
178 \newlength\AMC@boxeddim
179 \define@key{AMCdim}{size}{\AMC@boxeddim=#1}
180 \define@key{AMCdim}{rule}{\AMC@boxedrule=#1}
181 \define@key{AMCdim}{down}{\AMC@boxeddown=#1}
182 \def\AMCboxDimensions#1{\setkeys{AMCdim}{#1}}
183 \AMCboxDimensions{size=2.5ex,down=.4ex,rule=.5pt}

```

\AMC@marque Command `\AMC@marque{<char>}{<filled>}` prints a box with character `<char>` inside, and filled if `<filled>` is non-empty, using global variables to identify the box (question and choice).

\AMCformBox It calls `\AMCformBox{<char>}{<filled>}{<trace>}{<key>}` to actually render the box. This last command can be customized by the user.

Command `\AMC@formBox` simply sets the first argument when empty before calling `\AMCformBox`.

```

184 \newcommand\AMCformBox[4]{%
185   \ifAMC@outside@box% letter to be written outside the box
186   \AMC@boxedchar{#3}{#4}{#2}\hspace{.1em}\textbf{#1}%
187   \else%
188     \AMC@boxedchar{#1}{#3}{#4}{#2}%
189   \fi%
190 }
191 \newcommand\AMC@formBox[4]{%
192   \AMCformBox{\ifx\@empty#1\@empty%
193     \AMCchoiceLabel{AMC@ncase}%
194     \else #1\fi}{#2}{#3}{#4}%
195 }
196 \newcommand{\AMC@marque}[2]{%
197   \ifAMC@ensemble%
198     \ifAMC@zoneformulaire% for codes inside form sheet
199       \protect\AMC@formBox{#1}{#2}{1}{case:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}%
200     \else%
201       \ifAMCformulaire@dedans% for answer boxes inside form sheet
202         \protect\AMC@formBox{#1}{#2}{1}{case:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}%
203       \else% outside form sheet: not to be read during data capture
204         \AMC@caselettre{#1}{-}{#2}%

```

```

205 \fi\fi%
206 \else% no separate sheet for answers: always read
207 \ifAMC@inside@box%
208 \AMC@caselettre{#1}{1}{case:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}{#2}%
209 \else%
210 \AMC@boxedchar{1}{1}{case:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}{#2}%
211 \fi%
212 \fi%
213 }

```

4.6.3 Binary boxes

The package prints on each page some boxes that code (like binary digits) student sheet number, page number and a check number, so as to be read easily from scans after exam.

`\AMCid@checkmax` The check number is just decreased each page. Its maximum value is `\AMCid@checkmax`. The number of binary digits used to print student sheet number, page and check number are `\AMC@NCBetud`, `\AMC@NCBpage` and `\AMC@NCBcheck`. The number of the first page is `\AMC@premierecopie`.
`\AMC@NCBcheck` The length of zone reserved for binary boxes is `\AMC@CBtaille`.

```

214 \def\AMCid@checkmax{60}
215 \def\AMC@NCBetud{12}
216 \def\AMC@NCBpage{6}
217 \def\AMC@NCBcheck{6}
218 \newlength{\AMC@CBtaille}\setlength{\AMC@CBtaille}{5cm}
219 \def\AMC@premierecopie{1}

```

`\AMC@binaryBoxes` Command `\AMC@binaryBoxes[⟨ndigits⟩]{⟨n⟩}` prints `⟨ndigits⟩` boxes to represent number `⟨n⟩` in its binary form. `\AMCbin@one` and `\AMCbin@zero` print individual digit-boxes.

For example, `\AMC@binaryBoxes[12]{367}` shows $367 = 000101101111_2$ using 12 boxes:



```

220 \newtoks\AMCbin@sequence
221 \newcount\AMCbin@number
222 \newcount\AMCbin@ndigits
223 \newcount\AMCbin@id
224 \newcount\AMCbin@digit
225 \def\AMCbin@one{\advance\AMCbin@digit\@ne%
226 \AMC@boxedchar{1}{chiffre:\the\AMCbin@id,\the\AMCbin@digit}{1}}
227 \def\AMCbin@zero{\advance\AMCbin@digit\@ne%
228 \AMC@boxedchar{1}{chiffre:\the\AMCbin@id,\the\AMCbin@digit}{}}
229 \def\AMCbin@begin#1{\AMCbin@id=#1\AMCbin@digit=\z@}
230 \newcommand{\AMC@binaryBoxes}[2][1]{%
231 {\AMCboxDimensions{size=.32cm,down=0pt,rule=.2pt}\AMCbin@sequence={}\AMCbin@number=#2\relax%
232 \AMCbin@ndigits=\z@%
233 \loop%
234 \ifnum\AMCbin@number>\z@%
235 \advance\AMCbin@ndigits\@ne%
236 \ifodd\AMCbin@number\AMCbin@sequence=\expandafter{\expandafter\AMCbin@one\the\AMCbin@sequence}%
237 \else\AMCbin@sequence=\expandafter{\expandafter\AMCbin@zero\the\AMCbin@sequence}\fi%

```

```

238 \divide\AMCbin@number\tw%
239 \repeat%
240 \loop\relax%
241 \ifnum\AMCbin@endigits<#1\advance\AMCbin@endigits\@ne%
242 \AMCbin@sequence=\expandafter{\expandafter\AMCbin@zero\the\AMCbin@sequence}\repeat%
243 \the\AMCbin@sequence%
244 }}

```

4.7 Handling groups of questions

The package allows to handle groups of questions, so as to be able to shuffle them before printing them to the sheets.

\nouveaugroupe Command `\nouveaugroupe{<group-name>}{<n>}` creates a new (empty) group with name `<group-name>` (argument `<n>` is present only for compatibility reasons and is ignored). Command `\element{<group-name>}{<text>}` adds to group `<group-name>` a new element that contains `<text>`. `<text>` can be a `question` environment, ore two successive `questions` to be kept together, or anything else. Calling command `\nouveaugroupe` is not compulsory, as `\element` calls it if necessary.

```

245 \newcount\AMCtok@k
246 \newcount\AMCtok@max
247 \newcommand{\nouveaugroupe}[2]{%
248   \expandafter\ifx\csname #1@k\endcsname\relax
249     \expandafter\newcount\csname #1@k\endcsname%
250     \csname #1@k\endcsname=\z@%
251   \fi%
252 }
253 \newcommand\AMC@prepare@element[1]{%
254   \nouveaugroupe{#1}{}%
255   \global\advance\csname #1@k\endcsname\@ne\relax%
256   \AMCtok@k=\csname #1@k\endcsname%
257   \expandafter\ifx\csname #1@romannumeral\AMCtok@k\endcsname\relax%
258     \expandafter\newtoks\csname #1@romannumeral\AMCtok@k\endcsname\fi%
259 }
260 \newcommand{\element}[2]{%
261   \AMC@prepare@element{#1}%
262   \csname #1@romannumeral\AMCtok@k\endcsname={#2}%
263 }

```

\shufflegroup Command `\shufflegroup{<group-name>}` shuffles the elements of group `<group-name>`. It can be called at each student sheet in order to get different student sheets and avoid cheating. Command **\insertgroup** `\insertgroup[<n>]{<groupname>}` inserts all the elements of group `<groupname>`, or only the first `<n>` elements if `<n>` is given.

```

264 \newcommand{\shufflegroup}[1]{%
265   {\AMC@shuffletoks{\number\csname #1@k\endcsname}{#1}}%
266 }
267 \newcount\AMCtok@ik
268 \newcommand{\insertgroup}[2][0]{%
269   \AMCtok@max=#1\relax%
270   \ifnum\the\AMCtok@max<1%

```

```

271 \AMCtok@max=\csname #2@k\endcsname%
272 \fi%
273 \AMCtok@ik=\z@%
274 {\loop%
275 \advance\AMCtok@ik\@ne\relax%
276 \the\csname #2@\romannumeral\AMCtok@ik\endcsname%
277 \ifnum\AMCtok@ik<\AMCtok@max\repeat}%
278 }

```

`\cleargroup` The commands `\cleargroup` and `\copygroup` can also be used to make more complex questions combinations in the exams, allowing for example to ask the package to shuffle 3 questions taken at random from group `groupa` and 5 questions taken at random from group `groupb`.

`\cleargroup{<group>}` clears the group `<group>`, ereasing all of its elements.

`\copygroup[<n>]{<from>}{<to>}` copies `<n>` elements from group `<from>` to group `<to>`. If optional parameter `<n>` is not given, all the questions from group `<from>` are copied.

See section 3.4 for an illustration for these commands.

```

279 \newcommand{\cleargroup}[1]{%
280 \nouveaugroupe{#1}{}%
281 \csname #1@k\endcsname=\z@%
282 }
283 \newcommand{\copygroup}[3][0]{%
284 \AMCtok@max=#1\relax%
285 \ifnum\the\AMCtok@max<1%
286 \AMCtok@max=\csname #2@k\endcsname%
287 \fi%
288 \AMCtok@ik=\z@%
289 {\loop%
290 \advance\AMCtok@ik\@ne\relax%
291 \AMC@prepare@element{#3}%
292 \global\csname #3@\romannumeral\AMCtok@k\endcsname=\csname #2@\romannumeral\AMCtok@ik\endcsname%
293 \ifnum\AMCtok@ik<\AMCtok@max\repeat}%
294 }

```

4.8 Questions

To manage multiple choice questions, first set some counters and token registers to handle answers. Token registers `\reponse@i`, `\reponse@ii` and so on will be used for answers – we restrict the number of answers of a single questions to `\AMCload@counter = 199`.

```

295 \newcount\AMCrep@count
296 \AMCload@counter=199
297 \@whilenum\AMCload@counter>0\do{%
298 \expandafter\newtoks\csname reponse@\romannumeral\AMCload@counter\endcsname%
299 \advance\AMCload@counter\m@ne%
300 }

```

`\AMCload@reponse` Command `\AMCload@reponse{<n>}{<text>}` will be used to add answer number `<n>` with text `<text>` (`<text>` will include the box to be ticked and all the layout commands) to the set of answers (in a token register `\reponse@xxx` – counter `\AMCload@counter` keeps track of the number of answers), in order to shuffle them when all answers will be loaded.

When answers are not to be shuffled, command `\AMCrien@deux{<n>}{<text>}` will be used instead, only printing `<text>`.

```

301 \newcommand\AMCload@reponse[2]{%
302   \advance\AMCload@counter\@ne\relax%
303   \csname reponse@\romannumeral\AMCload@counter\endcsname%
304   =\expandafter{\expandafter\AMCrep@count\expandafter=#2 #1}%
305 }
306 \newcommand\AMCrien@deux[2]{#1}

```

`\shuffle@it` After loading all answers, commands `\shuffle@it` will be used to shuffle them, and `\AMCdump@reponses` to print them.

```

307 \def\shuffle@it{\AMC@shuffletoks{\number\AMCload@counter}{reponse@}}
308 \newcount\AMCnum@questions
309 \newcommand\AMCdump@reponses{%
310   \global\AMCnum@questions=\AMCload@counter%
311   \@whilenum\AMCload@counter>0\do{%
312     \the\csname reponse@\romannumeral\AMCload@counter\endcsname%
313     \advance\AMCload@counter\m@ne}}

```

4.8.1 Managing answers

`\lastchoices` Command `\AMCrep@init{<mode>}` is called for each question before reading answers. `<mode>` is `r` for suffled answers, and `o` if answers are not to be shuffled. It sets the number of answers counter to zero, and calls `\AMCrep@o` or `\AMCrep@r` depending on `<mode>`. These commands sets `\AMCload@@reponse` and `\AMCrep@fini` that will be called for each answer and after the last answer respectively, depending on `<mode>`:

- If `<mode>=r`, `\AMCload@@reponse` is `\AMCload@reponse` (loads answer to token register) and `\AMCrep@fini` calls `\shuffle@it` and `\AMCdump@reponses`;
- If `<mode>=o`, `\AMCload@@reponse` is `\AMCrien@deux` (prints answer directly) and `\AMCrep@fini` does nothing.

Command `\lastchoices` is called before giving answers that are to be printed at the end (even when shuffling answers). It closes the answers list calling `\AMCrep@fini` and opens another one in ordered mode. Note that it also saves the value of `\AMCrep@count`, which is the number of the current answer among all answers given in the subject source for the current question.

Command `\AMC@fin@rep` is to be called after the last answer: it adds a “None of these answers are correct.” answer if necessary (package option `completemulti`) with answer number zero, and calls `\AMCrep@fini`.

```

314 \newcommand\AMCrep@init[1]{%
315   \ifAMC@ordre\AMCrep@o\else%
316     \csname AMCrep@#1\endcsname\fi\AMCload@counter=\z@}
317 \newcommand\AMCrep@o{%
318   \def\AMCload@@reponse{\AMCrien@deux}\def\AMCrep@fini{}}
319 \newcommand\AMCrep@r{%
320   \def\AMCload@@reponse{\AMCload@reponse}%
321   \def\AMCrep@fini{\shuffle@it\AMCdump@reponses}}
322 \newcount\AMCrep@@count

```

```

323 \newcommand\lastchoices{%
324   \AMCrep@count=\AMCrep@count%
325   \AMCrep@fini\AMCrep@init{o}%
326   \AMCrep@count=\AMCrep@count}
327 \newcommand\@aucune{\emph{\AMC@loc@none}}
328 \newcommand\AMC@fin@rep{%
329   \ifAMCcomplete@multi\ifAMCtype@multi%
330     \lastchoices\AMCrep@count=-1%
331     \ifAMCune@bonne\wrongchoice{\@aucune}\else%
332       \ifAMC@postcorrect\wrongchoice{\@aucune}\else\correctchoice{\@aucune}\fi%
333     \fi\fi\fi\AMCrep@fini}

```

4.8.2 Separate answer sheet

This package needs some memory to print questions/answers boxes again on a separate answer sheet.

`\AMCformQuestion` First define commands that will announce questions and answers on the separate answer sheet (these commands can be modified by the user): `\AMCformQuestion{<n>}` is responsible for announcing question number `<n>`, and `\AMCformAnswer{<box>}` is responsible for printing the box to be ticked, given as argument `<box>`.

Commands `\AMCformQuestionA` and `\AMCformAnswerA` set up counter `\AMC@ncase` value before calling their counterparts.

```

334 \def\AMCmem@ireData{}
335 \def\AMCformQuestion#1{\vspace{\AMCformVSpace}\par{\AMC@loc@qf{#1}}}
336 \def\AMCformQuestionA#1{\setcounter{AMC@ncase}{0}\AMCformQuestion{#1}}
337 \def\AMCformAnswer#1{\hspace{\AMCformHSpace} #1}
338 \def\AMCformAnswerA#1{\addtocounter{AMC@ncase}{1}\AMCformAnswer{#1}}

```

`\AMCmem@ireAJ` These are commands to manage memory for separate answer sheet. `\AMCmem@ireAJ{<code>}` adds `<code>` to this memory. `\AMCmem@ireAJRep{<code>}` adds to memory answer code `<code>`, and `\AMCform` `\AMCmem@ireQ{<n>}` adds to memory question code to announce question number `<n>`.

`\AMCformS` The command `\AMCformBegin` defines the beginning of the separate answer sheet for the current student sheet, and `\AMCform` prints the whole memory: questions and answers boxes.

`\AMCformS` is a `\AMCform` variant that does not clear the list of answer boxes. It can be used to make the same exact subject for all students, displaying the questions before (outside) `onecopy`, so that `onecopy` contains only the answer sheet.

```

339 \newcommand\AMCmem@ireAJ[1]{%
340   \ifAMC@ensemble\ifAMC@zoneformulaire\else%
341     \begingroup\AMCformulaire@dedanstrue%
342     \let\protect\unexpandable\protect%
343     \global\edef\AMCmem@ireData{\AMCmem@ireData #1}%
344     \endgroup\fi\fi}
345 \newcommand\AMCmem@ireAJRep[1]{%
346   \addtocounter{AMC@ncase}{1}\AMCmem@ireAJ{\protect\AMCformAnswerA{#1}}}
347 \newcommand\AMCmem@ireQ[1]{\AMCmem@ireAJ{\protect\AMCformQuestionA{#1}}}
348 \def\AMCformBegin{\AMC@zoneformulairetrue}

```

```

349 \newcommand\AMCform{%
350   \ifAMC@ensemble\AMCformulaire@dedanstrue\AMCmem@ireData%
351   \global\def\AMCmem@ireData{}\fi}
352 \newcommand\AMCformS{%
353   \ifAMC@ensemble\AMCformulaire@dedanstrue%
354   \AMC@amclog{AUTOQCM[BR=0]^^J}\AMCmem@ireData%
355   \fi}

```

4.8.3 Formatting answers

`choices` Answers have to be included in an environment `choices` (standard), `choiceshoriz` (answers on one line) or `choicescustom` (user defined) depending on the desired formatting.

`choicescustom` Use `\AMCBoxedAnswers` to request all answers to be included in L^AT_EX boxes; this can be useful for example when using multicolumn answers formatting.

```

356 \def\AMCBoxedAnswers{\AMC@rbloctrue}
357 \newenvironment{choices}[1][r]{%
358   \AMCrep@count=\z@\def\une@rep{\AMCrep@itemize}%
359   \ifAMC@rbloc\def\une@rep{\AMCrep@bloc}%
360   \else\begin{itemize}\setlength{\itemsep}{\AMCinterIrep}\fi%
361   \AMCrep@init{#1}}%
362   {\AMC@fin@rep\ifAMC@rbloc\else\end{itemize}\fi}
363 \newenvironment{choiceshoriz}[1][r]{%
364   \AMCrep@count=\z@\def\une@rep{\AMCrep@ligne}\AMCrep@init{#1}%
365   \par\begin{center}}%
366   {\AMC@fin@rep\end{center}}
367 \newenvironment{choicescustom}[1][r]{%
368   \AMCrep@count=\z@\def\une@rep{\AMCrep@perso}\AMCrep@init{#1}%
369   \AMCbeginAnswer\ignorespaces}%
370   {\AMC@fin@rep\AMCendAnswer}

```

`\AMCrep@bloc` For each of these styles, a corresponding `\AMCrep@xxx{<box>}{<text>}` is defined, which will format the answer with a box given in `<box>` and text `<text>`. `\AMCrep@bloc` is also defined and used in standard formatting when the user wants to put answers inside a L^AT_EX box.

```

\AMCrep@itemize
\AMCrep@ligne
\AMCrep@perso
371 \newcommand\AMCrep@bloc[2]{\AMCmem@ireAJRep{#1}%
372   \par\noindent\begin{minipage}{\linewidth}%
373   \begin{itemize}\item[#1] #2\end{itemize}\end{minipage}%
374   \vspace{\AMCinterBrep}}
375 \newcommand\AMCrep@itemize[2]{\AMCmem@ireAJRep{#1}\item[#1] #2}
376 \newcommand\AMCrep@ligne[2]{\AMCmem@ireAJRep{#1}%
377   \mbox{#1\hspace*{1em}#2}\hspace{3em plus 4em}}
378 \newcommand\AMCrep@perso[2]{\AMCmem@ireAJRep{#1}\AMCanswer{#1}{#2}}

```

`\AMCbeginAnswer` The custom style will use user-defined commands to format answers: `\AMCbeginAnswer` is called once before answers, `\AMCanswer{<box>}{<text>}` is called for each answer (`<box>` being the box to be ticked and `<text>` the text associated with the proposed answer), and `\AMCendAnswer` is called after all answers.

```

379 \def\AMCbeginAnswer{}
380 \def\AMCanswer#1#2{#1 #2}
381 \def\AMCendAnswer{}

```


`\correctchoice` The commands `\correctchoice` and `\wrongchoice` are used inside `choices`-like environments to give the proposed answers and specify if they are to be ticked by the students or not.

```

382 \newcommand{\correctchoice}[2] [] {\advance\AMCrep@count\@ne\relax%
383   \ifAMC@calibration\AMC@amclog{AUTOQCM[REP=\the\AMCrep@count:B]^^J}\fi%
384   \global\AMCune@bonnettrue%
385   \AMCload@@reponse{\une@rep{\ifAMC@correc\AMC@marque{#1}{1}%
386     \else\AMC@marque{#1}{\fi}{#2}}{\the\AMCrep@count}\ignorespaces}
387 \newcommand{\wrongchoice}[2] [] {\advance\AMCrep@count\@ne\relax%
388   \ifAMC@calibration\AMC@amclog{AUTOQCM[REP=\the\AMCrep@count:M]^^J}\fi%
389   \AMCload@@reponse{\une@rep{\AMC@marque{#1}{}}{#2}}{\the\AMCrep@count}%
390   \ignorespaces}

```

4.8.4 Formatting questions

`\AMCquestionaff` The counter `\AMCquestionaff` keeps track of the current question number. It can be redefined by the user, for example to print several questions without a number, and then print questions with a number starting at one.

`\AMC@qaff` will increase this counter and format the question number out.

```

391 \newcounter{AMCquestionaff}
392 \newcommand{\AMCnumero}[1]{\setcounter{AMCquestionaff}{#1}\addtocounter{AMCquestionaff}{-1}}
393 \newcommand\AMC@qaff{\addtocounter{AMCquestionaff}{1}\arabic{AMCquestionaff}}

```

`\AMCbeginQuestion` The command `\AMCbeginQuestion{<n>}{<sign>}` will format the question header, where `<n>` is the question number and `<sign>` being `\multiSymbole` in case of a multiple question, and empty in case of a simple one. `\AMCbeginQuestion` and `\multiSymbole` can be user-redefined.

```

394 \def\AMCbeginQuestion#1#2{\par\noindent\AMC@loc@q{#1}{#2}\hspace*{1em}}
395 \def\multiSymbole{${\clubsuit}$}

```

`question` Environment `{question}{<key>}` encloses a simple question (with one and only one correct choice) with associated unique key `<key>` and the proposed answers.

`questionmult` Environment `{questionmult}{<key>}` is the same for multiple questions (with none, one or several correct choices).

`questionouverte` Environment `{questionouverte}[<width>]` is used for open questions (that won't be marked automatically!), with width given as an optional argument (defaults to 3 cm).

```

396 \ifx\question\undefined\else\let\question\undefined\fi
397 \def\AMCnobloc{\AMC@qblocfalse}
398 \def\AMCbloc{\AMC@qbloctrue}
399 \newenvironment{question}[2] [] {%
400   \global\def\AMCid@name{#2}\AMC@affecte{#2}{\AMCid@quest}%
401   \ifAMC@calibration\AMCmessage{Q=\the\AMCid@quest}\fi%
402   \AMCtype@multifalse\ifAMC@qbloc\noindent\begin{minipage}{\linewidth}\fi%
403   \ifAMC@affichekeys\index{\texttt{#2}}\fi%
404   \AMCbeginQuestion{\ifAMC@affichekeys[\texttt{#2}]\else\AMC@qaff\fi}{#1}%
405   \AMCformulaire@dedansfalse\setcounter{AMC@ncase}{0}%
406   \AMCmem@ireQ{\arabic{AMCquestionaff}}}%
407 {\ifAMC@qbloc\end{minipage}\vspace{3ex}\fi\AMCmessage{FQ}}
408 \newenvironment{questionmult}[1] {%
409   \AMCune@bonnefalse\begin{question}[{\multiSymbole}]{#1}%

```

```

410 \AMCtype@multitrue\ifAMC@calibration%
411 \AMC@amclog{AUTOQCM[MULT]^^J}\fi}%
412 {\end{question}}
413 \newdimen\ouverte@vs
414 \newenvironment{questionouverte}[1][3cm]{%
415 \AMCtype@multifalse\ouverte@vs=#1%
416 \ifAMC@qbloc\noindent\begin{minipage}{\linewidth}\fi%
417 \AMCbeginQuestion{\AMC@qaff}{}}%
418 {\vspace*{\ouverte@vs}\ifAMC@qbloc\end{minipage}\vspace{3ex}\fi}

```

4.9 Scoring

\scoring Scoring strategies are simply transmitted to the .amc file for later analysis.

\scoringDefaultS \scoring{<score>} details the scoring strategy for current question or current answer,
\scoringDefaultM \scoringDefaultS{<score>} and \scoringDefaultM{<score>} gives default scoring strategy for
QuestionIndicative simple and multiple questions, and \QuestionIndicative tells that the current question is not
no be taken into account in the global mark.

```

419 \def\scoring#1{\ifAMC@calibration\AMC@amclog{AUTOQCM[B=#1]^^J}\fi}
420 \def\scoringDefaultS#1{\ifAMC@calibration\AMC@amclog{AUTOQCM[BDS=#1]^^J}\fi}
421 \def\scoringDefaultM#1{\ifAMC@calibration\AMC@amclog{AUTOQCM[BDM=#1]^^J}\fi}
422 \def\QuestionIndicative{\ifAMC@calibration\AMC@amclog{AUTOQCM[INDIC]^^J}\fi}

```

4.10 Codes

`\AMCcode` Students can code some numerical information (such as student number) through special questions, which can be formatted easily with the command `\AMCcode{<key>}{<ndigits>}`, where `<key>` is a key prefix and `<ndigits>` is the number of required digits. The digits entered by the student will be available through the questions `<key>.1, \dots, <key>.<ndigits>`.

As an example, `\AMCcode{code}{6}` produces the opposite boxes (two results are show here: without or with `separateanswersheet` option), and trace positions of all the boxes in the `.xy` file with the `code` identifier: the first digit is represented by question with key `code.6`, the second by question with key `code.5`, and so on.

Positions of the boxes are logged in the `.xy` file, as shown in section 5.3 for the first set of boxes (without `separateanswersheet`, with digits outside boxes).

0	0	0	0	0	0
1	1	1	1	1	1
2	2	2	2	2	2
3	3	3	3	3	3
4	4	4	4	4	4
5	5	5	5	5	5
6	6	6	6	6	6
7	7	7	7	7	7
8	8	8	8	8	8
9	9	9	9	9	9

0	0	0	0	0	0
1	1	1	1	1	1
2	2	2	2	2	2
3	3	3	3	3	3
4	4	4	4	4	4
5	5	5	5	5	5
6	6	6	6	6	6
7	7	7	7	7	7
8	8	8	8	8	8
9	9	9	9	9	9

The “horizontal” version `\AMCcodeH` can also be considered, specially with a small number of digits. See opposite for the result of `\AMCcodeH{code}{3}`.

0	1	2	3	4	5	6	7	8	9
0	1	2	3	4	5	6	7	8	9
0	1	2	3	4	5	6	7	8	9

```

423 \newcount\AMC@chiffres
424 \newdimen\AMCcodeHspace\AMCcodeHspace=.5em
425 \newdimen\AMCcodeVspace\AMCcodeVspace=.5em
426 \newdimen\AMCcodeBoxSep\AMCcodeBoxSep=.1em
427 \newcommand{\AMCcode}[2]{%
428 {\def\AMCbeginQuestion##1##2{}%
429 \setlength{\parindent}{0pt}%
430 \def\AMCbeginAnswer{\hspace{0pt}%
431 \vbox\bgroup}%
432 \def\AMCendAnswer{\vspace{-\AMCcodeVspace}\egroup%
```

```

433 \hspace{\AMCcodeHspace}}%
434 \def\AMCanswer##1##2{\hbox{##1\ifAMC@ensemble\else%
435 \ifAMC@inside@box\else\hspace{\AMCcodeBoxSep}\textbf{##2}}\fi\fi\hspace*{\fill}}%
436 \vspace{\AMCcodeVspace}}%
437 \AMCnobloc%
438 \AMC@chiffres=#2\loop%
439 \begin{question}{#1.\the\AMC@chiffres}\QuestionIndicative%
440 \begin{choicescustom}[o]\scoring{auto=0}%
441 \wrongchoice[0]{0}%
442 \wrongchoice[1]{1}%
443 \wrongchoice[2]{2}%
444 \wrongchoice[3]{3}%
445 \wrongchoice[4]{4}%
446 \wrongchoice[5]{5}%
447 \wrongchoice[6]{6}%
448 \wrongchoice[7]{7}%
449 \wrongchoice[8]{8}%
450 \wrongchoice[9]{9}%
451 \end{choicescustom}%
452 \end{question}%
453 \advance\AMC@chiffres\m@ne\ifnum\AMC@chiffres>0\repeat%
454 \hspace{-\AMCcodeHspace}%
455 }}
456 \newcommand{\AMCcodeH}[2]{%
457 {\def\AMCbeginQuestion##1##2}%
458 \setlength{\parindent}{0pt}%
459 \def\AMCbeginAnswer{\hbox\bgroup}%
460 \def\AMCendAnswer{\egroup\vspace{\AMCcodeVspace}\par}%
461 \def\AMCanswer##1##2{\hbox{##1\ifAMC@ensemble\else%
462 \ifAMC@inside@box\else\hspace{\AMCcodeBoxSep}\textbf{##2}}\fi\fi}%
463 \hspace{\AMCcodeHspace}}%
464 \AMCnobloc%
465 \AMC@chiffres=#2\loop%
466 \begin{question}{#1.\the\AMC@chiffres}\QuestionIndicative%
467 \begin{choicescustom}[o]\scoring{auto=0}%
468 \wrongchoice[0]{0}%
469 \wrongchoice[1]{1}%
470 \wrongchoice[2]{2}%
471 \wrongchoice[3]{3}%
472 \wrongchoice[4]{4}%
473 \wrongchoice[5]{5}%
474 \wrongchoice[6]{6}%
475 \wrongchoice[7]{7}%
476 \wrongchoice[8]{8}%
477 \wrongchoice[9]{9}%
478 \end{choicescustom}%
479 \end{question}%
480 \advance\AMC@chiffres\m@ne\ifnum\AMC@chiffres>0\repeat%
481 }}

```

4.10.1 Intervals

`\AMCIntervals` The command `\AMCIntervals{⟨x⟩}{⟨x0⟩}{⟨x1⟩}{⟨delta⟩}` can be used to present answers as intervals $[x_i, x_i + \delta[$ covering $[\langle x0 \rangle, \langle x1 \rangle]$, such that the only interval containing $\langle x \rangle$ is declared as `\wrightchoice`, and the other as `\wrongchoice`.

For this command to work, one has to load package `fp`.

As an example,

```
\begin{question}{quarter}
  In which interval falls  $1/4$ ?
  \begin{multicols}{5}
    \begin{choices}[o]
      \AMCIntervals{0.25}{0}{1}{0.1}
    \end{choices}
  \end{multicols}
\end{question}
```

produces (in correction mode):

Question 2 In which interval falls $1/4$?

<input type="checkbox"/> $[0, 0.1[$	<input checked="" type="checkbox"/> $[0.2, 0.3[$	<input type="checkbox"/> $[0.4, 0.5[$	<input type="checkbox"/> $[0.6, 0.7[$	<input type="checkbox"/> $[0.8, 0.9[$
<input type="checkbox"/> $[0.1, 0.2[$	<input type="checkbox"/> $[0.3, 0.4[$	<input type="checkbox"/> $[0.5, 0.6[$	<input type="checkbox"/> $[0.7, 0.8[$	<input type="checkbox"/> $[0.9, 1[$

```
482 \def\AMC@intervx#1#2{\AMC@CI@cas{[#1,\,#2[]}}
483 \def\AMCIntervals#1#2#3#4{%
484 \FPeval\AMC@CI@a{clip(#2)}%
485 \let\AMC@CI@cas=\wrongchoice%
486 \loop%
487 \FPeval\AMC@CI@b{clip(AMC@CI@a + #4)}%
488 \FPiflt{#1}\AMC@CI@b\let\AMC@CI@cas=\correctchoice\fi%
489 \FPiflt{#1}\AMC@CI@a\let\AMC@CI@cas=\wrongchoice\fi%
490 \@expandtwoargs\AMC@intervx{\AMC@CI@a}{\AMC@CI@b}%
491 \FPiflt\AMC@CI@b{#3}%
492 \FPset\AMC@CI@a{\AMC@CI@b}%
493 \repeat}
```

4.11 Page formatting

4.11.1 Watermark

`\AMCw@termark` These commands are used to print a grey “DRAFT” under each page, so as to prevent from printing old versions of the subject.

```
494 \DeclareFontShape{OT1}{cmr}{b}{n}{<35->cmr17}{-}
495 \def\AMC@watertext{\AMC@loc@draft}
496 \newcommand\AMCw@termark{%
497 \setlength{\@tempdimb}{.5\paperwidth}%
498 \setlength{\@tempdimc}{-.5\paperheight}%
499 \put(\strip@pt\@tempdimb,\strip@pt\@tempdimc){%
500 \makebox(0,0){\rotatebox{45}{\AMC@LR{%
```

```

501      \textcolor[gray]{0.8}{
502      \fontencoding{OT1}\fontfamily{cmr}
503      \fontseries{b}\fontshape{n}
504      \fontsize{90pt}{120pt}
505      \selectfont
506      \AMC@watertext}}}}}}
507 \newcommand\AMCw@terprint[1]{%
508   \setbox\@tempboxa\vbox to \z@{%
509     \vbox{%
510       \hbox to \z@{%
511         #1\hss}}\vss}
512   \dp\@tempboxa\z@
513   \box\@tempboxa}

```

4.11.2 Signs for scan analysis

The following code sets up all the signs to be printed on the pages so as to be able to recognize the position of the boxes on the scans. Four circles ● are printed on the corners (see \m@rqueCalage), and binary boxes show the student sheet number, the page and a checking number.

\AMC@intituleHead is the title to be printed at the beginning (used for corrected sheet, and empty on subject). \AMC@note is printed at the bottom of each page.

```

514 \def\AMCcercle#1#2{%
515   {\setlength{\unitlength}{1mm}%
516     \begin{picture}(\#1,\#1)(-#2,-#2)\thinline\circle*{\#1}\end{picture}}}
517 \def\m@rqueCalage{\AMCcercle{3.6}{1.8}}
518 \def\m@rque#1{\AMC@tracebox{1}{\#1}{\m@rqueCalage}}
519 \def\he@dtaille#1{\vbox to 1cm{\#1}}
520 \def\he@dbas#1{\he@dtaille{\vspace*{\fill}\#1}}
521 \def\he@dhaut#1{\he@dtaille{\#1\vspace*{\fill}}}
522 \def\AMC@intituleHead{\AMC@loc@corrected}
523 \def\AMC@note{}
524 \AtBeginPage{\ifAMC@pagelayout\global\advance\AMCid@check\m@ne%
525   \ifnum\AMCid@check<1\global\AMCid@check=\AMCid@checkmax\fi%
526   \AMC@pagepos%
527   \ifAMC@watermark\ifAMC@correthead\else\AMCw@terprint{\AMCw@termark}%
528   \fi\fi\fi}
529 \AtBeginDocument{%
530   \ifAMC@pagelayout%
531     \pagestyle{fancy}
532     \renewcommand{\headrulewidth}{0pt}
533     \ifAMC@correthead
534       \fancyhf{}\fancyhead[C]{\textsc{\AMC@intituleHead}}
535     \else
536       \fancyhf{}
537       \fancyhead[L]{\AMC@LR{\he@dbas{\leavevmode\m@rque{positionHG}}}}
538       \fancyhead[R]{\AMC@LR{\he@dbas{\leavevmode\m@rque{positionHD}}}}
539       \fancyfoot[L]{\AMC@LR{\leavevmode\m@rque{positionBG}}}
540       \fancyfoot[R]{\AMC@LR{\leavevmode\m@rque{positionBD}}}
541       \fancyhead[C]{\AMC@LR{\he@dhaut{%

```

```

542     \begin{minipage}[b]{\AMC@CBtaille}
543     \AMCbin@begin{1}\noindent%
544     \AMC@binaryBoxes[\AMC@NCBetud]{\the\AMCid@etud}\\
545     \AMCbin@begin{2}\noindent%
546     \AMC@binaryBoxes[\AMC@NCBpage]{\thepage}\ignorespaces%
547     \AMCbin@begin{3}\AMC@binaryBoxes[\AMC@NCBcheck]{\the\AMCid@check}%
548     \end{minipage}
549     \hbox to 4cm{\hspace*{\fill}%
550     \texttt{+\the\AMCid@etud/\thepage/\the\AMCid@check+}}%
551   }}}
552   \fancyhfoffset[EOLR]{5mm}
553   \fi
554   \fancyfoot[C]{\AMC@note}
555   \fi
556 }

```

4.12 Defining a single exam copy content

\onecopy The command `\onecopy[$\langle n \rangle$]{ $\langle code \rangle$ }` generates $\langle n \rangle$ copies of the subject that is described in $\langle code \rangle$. The L^AT_EX code $\langle code \rangle$ that generates a single copy can be a little long, so that the environment `examcopy` is often preferred.

```

557 \newcommand{\onecopy}[2]{%
558   \ifx\AMCNombreCopies\undefined\AMCnum@copies=#1%
559   \else\AMCnum@copies=\AMCNombreCopies\fi%
560   \AMC@amclog{AUTOQCM[TOTAL=\the\AMCnum@copies]^^J}%
561   \AMCid@etud=\AMC@premierecopie%
562   \AMCid@etudfin=\AMCnum@copies%
563   \advance\AMCid@etudfin by \AMC@premierecopie\relax%
564   \ifAMC@correchad\AMCid@etudfin=\AMC@premierecopie\fi
565   \loop%
566     \AMC@zoneformulairefalse\setcounter{page}{1}%
567     \AMCnumero{1}%
568     \ifAMC@calibration\AMC@amclog{AUTOQCM[ETU=\the\AMCid@etud]^^J}\fi%
569     #2\clearpage\advance\AMCid@etud\@ne\ifnum\AMCid@etud<\AMCid@etudfin\repeat%
570 }

```

\AMCcleardoublepage If you want to print the subject all at one time in duplex mode, it is necessary to end each subject with an even number of pages. This can be achieved using `\AMCcleardoublepage` at the end of the copy definition. This command is also usefull inserted before the separate answer sheet (if any).

```

571 \def\AMCcleardoublepage{\ifodd\thepage\clearpage~\fi\clearpage}

```

\exemplairepair To make some differences in the copies, checking if the student sheet number is odd, with `\exemplairepair` construct, can be usefull.

```

572 \def\exemplairepair{\ifodd\AMCid@etud}

```

\AMClabel **\AMCref** Commands `\AMCref` and `\AMClabel` replaces L^AT_EX's `\label` and `\ref` to be able to use different labels for different sheets.

```

573 \def\AMClabel#1{\expandafter\label{\the\AMCid@etud-#1}}
574 \def\AMCref#1{\expandafter\ref{\the\AMCid@etud-#1}}

```

4.13 Package options

See section 3.1 for the options descriptions.

```
575 \DeclareOptionX{noshuffle}{\AMC@ordretrue}
576 \DeclareOptionX{answers}{\AMC@corretheadtrue\AMC@correcttrue}
577 \DeclareOptionX{indivanswers}{\AMC@correcttrue}
578 \DeclareOptionX{box}{\AMC@qbloctrue}
579 \DeclareOptionX{separateanswersheet}{\AMC@ensembletrue}
580 \DeclareOptionX{digits}{\AMC@inside@digittrue}
581 \DeclareOptionX{ordre}{\AMC@ordretrue}
582 \DeclareOptionX{correc}{\AMC@corretheadtrue\AMC@correcttrue}
583 \DeclareOptionX{modele}{\AMC@corretheadtrue\AMC@correcfalse\AMC@ordretrue}
584 \DeclareOptionX{correcindiv}{\AMC@correcttrue}
585 \DeclareOptionX{init}{\AMC@SR@time}
586 \DeclareOptionX{bloc}{\AMC@qbloctrue}
587 \DeclareOptionX{completemulti}{\AMC@complete@multitrue}
588 \DeclareOptionX{insidebox}{\AMC@inside@boxtrue}
589 \DeclareOptionX{ensemble}{\AMC@ensembletrue}
590 \DeclareOptionX{chiffres}{\AMC@inside@digittrue}
591 \DeclareOptionX{outsidebox}{\AMC@outside@boxtrue}
592 \DeclareOptionX{calibration}{\AMC@calibrationtrue}
593 \DeclareOptionX{nowatermark}{\AMC@watermarkfalse}
594 \DeclareOptionX{catalog}{\AMC@watermarkfalse\AMC@corretheadtrue%
595   \AMC@correcttrue\AMC@ordretrue%
596   \def\AMC@intituleHead{\AMC@loc@catalog}\AMC@affichekeystrue}
597 \DeclareOptionX{francais}{\AMC@loc@FR}
598 \DeclareOptionX{lang}{\csname AMC@loc@#1\endcsname}
599 \DeclareOptionX{versionA}{%
600   \def\AMCid@checkmax{31}\def\AMC@NCBetud{9}\def\AMC@NCBpage{4}%
601   \def\AMC@NCBcheck{5}\setlength{\AMC@CBtaille}{4cm}%
602   \def\AMC@premierecopie{100}}
603 \DeclareOptionX{plain}{\AMC@plaintrue}
604 \DeclareOptionX{nopage}{\AMC@pagelayoutfalse}
605 \DeclareOptionX{postcorrect}{\AMC@postcorrecttrue}
606 \ProcessOptionsX
```

4.14 Optional features

This package tries to see if optional packages `environ` and `etex` are loadable, and load them if possible. This behaviour can be cancelled by using `plain` option.

```
607 \ifAMC@plain
608 \else
609   \IfFileExists{environ.sty}{\RequirePackage{environ}}{}
610   \ifx\TeXversion\@undefined
611     \else
612       \RequirePackage{etex}
613   \fi
614 \fi
```


`examcopy` Then, if `environ` package is loaded and defines command `\NewEnviron`, environment `examcopy` is defined.

Environment `{examcopy}[\langle n \rangle]` does the same as command `onecopy`: it encloses L^AT_EX code which makes *one* exam copy. Optional argument $\langle n \rangle$ gives the number of desired copies – this can also be modified redefinig `\AMCNombreCopies`.

```

615 \@ifpackageloaded{environ}{%
616   \ifx\NewEnviron\undefined\PackageWarning{automultiplechoice}%
617     {Package environ loaded but too old version:
618       environnement examcopy/copieexamen will NOT be defined.}%
619   \else\NewEnviron{examcopy}[1][5]{\onecopy{#1}{\BODY}}\fi}%
620 {\PackageWarning{automultiplechoice}%
621   {Package environ not loaded: environnement
622     examcopy/copieexamen will NOT be defined.}}
```

4.15 External control

`\SujetExterne` Some of the package options can be controlled defining `\xxxExterne` commands. For example, the following command will format the subject document, whatever options are used in the L^AT_EX file:

`\CalibrationExterne` pdf_latex '\nonstopmode\def\SujetExterne{1}\def\NoWatermarkExterne{1}\input{mcq.tex}'

`\CorrigeExterne`

`\CorrigeIndivExterne`

`\NoWatermarkExterne`

```

623 \ifx\SujetExterne\undefined\else
624 \message{***SUJET***^^J}
625 \AMC@calibrationtrue\AMC@correcfalse\AMC@corretheadfalse\AMC@watermarkfalse
626 \fi
627 \ifx\CalibrationExterne\undefined\else
628 \message{***CALIBRATION***^^J}
629 \AMC@calibrationtrue\AMC@correcfalse\AMC@corretheadfalse\AMC@watermarkfalse
630 \fi
631 \ifx\CorrigeExterne\undefined\else
632 \message{***CORRIGE***^^J}
633 \AMC@calibrationfalse\AMC@corretheadtrue\AMC@correcttrue\AMC@watermarkfalse
634 \fi
635 \ifx\CorrigeIndivExterne\undefined\else
636 \message{***CORRIGE***^^J}
637 \AMC@correcttrue\AMC@watermarkfalse
638 \fi
639 \ifx\NoWatermarkExterne\undefined\else
640 \AMC@watermarkfalse
641 \fi
```

4.16 Page layout

The following code sets the correct page layout to have room for signs for scan analysis, and prepares watermark printing:

```

642 \@ifpackageloaded{geometry}{\usepackage{geometry}}
643 \ifAMC@pagelayout
644   \ifAMC@correthead
645     \geometry{hmargin=3cm,vmargin={1cm,1cm},includeheadfoot,headheight=1cm,footskip=1cm}
```

```

646 \else
647 \geometry{hmargin=3cm,headheight=2cm,headsep=.3cm,footskip=1cm,top=3.5cm,bottom=2.5cm}
648 \fi
649 \ifAMC@watermark
650 \ifAMC@correthead\else
651 \def\AMC@note{\begin{minipage}{0.65\linewidth}
652 \AMC@LR{\textcolor{blue}{\AMC@loc@message}}
653 \end{minipage}}
654 }
655 \fi
656 \fi
657 \fi

```

4.17 Initialisation

Initialisation of the check counter:

```

658 \AMCid@check=\AMCid@checkmax\advance\AMCid@check\@ne

```

Telling outside if separate answer sheet, and boxes labelling, are requested:

```

659 \ifAMC@ensemble\AMC@amclog{AUTOQCM[VAR:ensemble=1]^^J}\fi
660 \ifAMC@inside@box\AMC@amclog{AUTOQCM[VAR:insidebox=1]^^J}\fi
661 \ifAMC@outside@box\AMC@amclog{AUTOQCM[VAR:outsidebox=1]^^J}\fi
662 \ifAMC@postcorrect\AMC@amclog{AUTOQCM[VAR:postcorrect=1]^^J}\fi

```

Preparing writing to .xy file :

```

663 \ifAMC@calibration
664 \newwrite\AMC@XYFILE%
665 \immediate\openout\AMC@XYFILE\jobname.xy%
666 \immediate\write\AMC@XYFILE{\string\version{\AMC@VERSION}}
667 \fi

```

4.18 French command names

For backward compatibility, a lot of commands have their french counterpart:

```

668 \let\reponses=\choices\let\endreponses=\endchoices
669 \let\reponseshoriz=\choiceshoriz\let\endreponseshoriz=\endchoiceshoriz
670 \let\reponsesperso=\choicescustom\let\endreponsesperso=\endchoicescustom
671 \let\bonne=\correctchoice
672 \let\mauvaise=\wrongchoice
673 \let\bareme=\scoring
674 \let\baremeDefaultM=\scoringDefaultM
675 \let\baremeDefaultS=\scoringDefaultS
676 \def\exemplaire{\AMC@loc@FR\onecopy}
677 \@ifpackageloaded{environ}{%
678 \let\copieexamen=\examcopy\let\endcopieexamen=\endexamcopy}{%
679 \let\melangegroupe=\shufflegroup
680 \let\restituegroupe=\insertgroup
681 \let\alafin=\lastchoices
682 \let\formulaire=\AMCform
683 \let\AMCdebutFormulaire=\AMCformBegin

```

```
684 \let\champnom=\namefield
685 \let\choixIntervalles=\AMCIntervals
```

5 Outputs

In the .xy file, $1/\langle n \rangle$ means student sheet number 1 (there is only one “student sheet” for this document as we did not use `\onecopy`) and page number $\langle n \rangle$ inside this student sheet. Then, each instance of the `\tracepos` command shows x and y positions as arguments #2 and #3 (unit is `sp`, such that $65536 \times 72.27 \text{ sp}$ is one inch). One has to take min and max of the x -values to determine the left and right position of the box, and min and max values of y -values to determine top and bottom position of the box.

5.1 namefield command

Lines in the .xy file from a `\namefield` command:

```
\tracepos{0/25:nom}{0sp}{32678096sp}
\tracepos{0/25:nom}{6038827sp}{0sp}
\tracepos{0/25:nom}{16026323sp}{0sp}
\tracepos{0/25:nom}{0sp}{29692918sp}
```

5.2 AMCboxedchar command

Lines in the .xy file from a `\AMCboxedchar` command:

```
\tracepos{0/25:test}{25491759sp}{21209196sp}
\tracepos{0/25:test}{26197179sp}{20503776sp}
```

5.3 AMCCode command

Lines in the .xy file from a `\AMCCode` command. Here, `code.\langle n \rangle:\langle q \rangle,\langle v \rangle` relates to digit number $\langle n \rangle$ from the right ($\langle n \rangle=1$ for units, $\langle n \rangle=2$ for tens, $\langle n \rangle=3$ for hundreds and so on), question number $\langle q \rangle$ (`\AMCCode` uses a fake question; this number can be ignored), and value $\langle v \rangle-1$ (box number $\langle v \rangle$ for the digit).

```
\tracepos{0/35:case:code.6:12,1}{21352659sp}{43949379sp}
\tracepos{0/35:case:code.6:12,1}{22058079sp}{43243959sp}
\tracepos{0/35:case:code.6:12,2}{21352659sp}{42835267sp}
\tracepos{0/35:case:code.6:12,2}{22058079sp}{42129847sp}
\tracepos{0/35:case:code.6:12,3}{21352659sp}{41721155sp}
\tracepos{0/35:case:code.6:12,3}{22058079sp}{41015735sp}
\tracepos{0/35:case:code.6:12,4}{21352659sp}{40607043sp}
\tracepos{0/35:case:code.6:12,4}{22058079sp}{39901623sp}
\tracepos{0/35:case:code.6:12,5}{21352659sp}{39492931sp}
\tracepos{0/35:case:code.6:12,5}{22058079sp}{38787511sp}
\tracepos{0/35:case:code.6:12,6}{21352659sp}{38378819sp}
\tracepos{0/35:case:code.6:12,6}{22058079sp}{37673399sp}
```

```

\tracepos{0/35:case:code.6:12,7}{21352659sp}{37264707sp}
\tracepos{0/35:case:code.6:12,7}{22058079sp}{36559287sp}
\tracepos{0/35:case:code.6:12,8}{21352659sp}{36150595sp}
\tracepos{0/35:case:code.6:12,8}{22058079sp}{35445175sp}
\tracepos{0/35:case:code.6:12,9}{21352659sp}{35036483sp}
\tracepos{0/35:case:code.6:12,9}{22058079sp}{34331063sp}
\tracepos{0/35:case:code.6:12,10}{21352659sp}{33922371sp}
\tracepos{0/35:case:code.6:12,10}{22058079sp}{33216951sp}
\tracepos{0/35:case:code.5:13,1}{22893665sp}{43949379sp}
\tracepos{0/35:case:code.5:13,1}{23599085sp}{43243959sp}
\tracepos{0/35:case:code.5:13,2}{22893665sp}{42835267sp}
\tracepos{0/35:case:code.5:13,2}{23599085sp}{42129847sp}
\tracepos{0/35:case:code.5:13,3}{22893665sp}{41721155sp}
\tracepos{0/35:case:code.5:13,3}{23599085sp}{41015735sp}
\tracepos{0/35:case:code.5:13,4}{22893665sp}{40607043sp}
\tracepos{0/35:case:code.5:13,4}{23599085sp}{39901623sp}
\tracepos{0/35:case:code.5:13,5}{22893665sp}{39492931sp}
\tracepos{0/35:case:code.5:13,5}{23599085sp}{38787511sp}
\tracepos{0/35:case:code.5:13,6}{22893665sp}{38378819sp}
\tracepos{0/35:case:code.5:13,6}{23599085sp}{37673399sp}
\tracepos{0/35:case:code.5:13,7}{22893665sp}{37264707sp}
\tracepos{0/35:case:code.5:13,7}{23599085sp}{36559287sp}
\tracepos{0/35:case:code.5:13,8}{22893665sp}{36150595sp}
\tracepos{0/35:case:code.5:13,8}{23599085sp}{35445175sp}
\tracepos{0/35:case:code.5:13,9}{22893665sp}{35036483sp}
\tracepos{0/35:case:code.5:13,9}{23599085sp}{34331063sp}
\tracepos{0/35:case:code.5:13,10}{22893665sp}{33922371sp}
\tracepos{0/35:case:code.5:13,10}{23599085sp}{33216951sp}
\tracepos{0/35:case:code.4:14,1}{24434671sp}{43949379sp}
\tracepos{0/35:case:code.4:14,1}{25140091sp}{43243959sp}
\tracepos{0/35:case:code.4:14,2}{24434671sp}{42835267sp}
\tracepos{0/35:case:code.4:14,2}{25140091sp}{42129847sp}
\tracepos{0/35:case:code.4:14,3}{24434671sp}{41721155sp}
\tracepos{0/35:case:code.4:14,3}{25140091sp}{41015735sp}
\tracepos{0/35:case:code.4:14,4}{24434671sp}{40607043sp}
\tracepos{0/35:case:code.4:14,4}{25140091sp}{39901623sp}
\tracepos{0/35:case:code.4:14,5}{24434671sp}{39492931sp}
\tracepos{0/35:case:code.4:14,5}{25140091sp}{38787511sp}
\tracepos{0/35:case:code.4:14,6}{24434671sp}{38378819sp}
\tracepos{0/35:case:code.4:14,6}{25140091sp}{37673399sp}
\tracepos{0/35:case:code.4:14,7}{24434671sp}{37264707sp}
\tracepos{0/35:case:code.4:14,7}{25140091sp}{36559287sp}
\tracepos{0/35:case:code.4:14,8}{24434671sp}{36150595sp}
\tracepos{0/35:case:code.4:14,8}{25140091sp}{35445175sp}
\tracepos{0/35:case:code.4:14,9}{24434671sp}{35036483sp}
\tracepos{0/35:case:code.4:14,9}{25140091sp}{34331063sp}

```

```

\tracepos{0/35:case:code.4:14,10}{24434671sp}{33922371sp}
\tracepos{0/35:case:code.4:14,10}{25140091sp}{33216951sp}
\tracepos{0/35:case:code.3:15,1}{25975677sp}{43949379sp}
\tracepos{0/35:case:code.3:15,1}{26681097sp}{43243959sp}
\tracepos{0/35:case:code.3:15,2}{25975677sp}{42835267sp}
\tracepos{0/35:case:code.3:15,2}{26681097sp}{42129847sp}
\tracepos{0/35:case:code.3:15,3}{25975677sp}{41721155sp}
\tracepos{0/35:case:code.3:15,3}{26681097sp}{41015735sp}
\tracepos{0/35:case:code.3:15,4}{25975677sp}{40607043sp}
\tracepos{0/35:case:code.3:15,4}{26681097sp}{39901623sp}
\tracepos{0/35:case:code.3:15,5}{25975677sp}{39492931sp}
\tracepos{0/35:case:code.3:15,5}{26681097sp}{38787511sp}
\tracepos{0/35:case:code.3:15,6}{25975677sp}{38378819sp}
\tracepos{0/35:case:code.3:15,6}{26681097sp}{37673399sp}
\tracepos{0/35:case:code.3:15,7}{25975677sp}{37264707sp}
\tracepos{0/35:case:code.3:15,7}{26681097sp}{36559287sp}
\tracepos{0/35:case:code.3:15,8}{25975677sp}{36150595sp}
\tracepos{0/35:case:code.3:15,8}{26681097sp}{35445175sp}
\tracepos{0/35:case:code.3:15,9}{25975677sp}{35036483sp}
\tracepos{0/35:case:code.3:15,9}{26681097sp}{34331063sp}
\tracepos{0/35:case:code.3:15,10}{25975677sp}{33922371sp}
\tracepos{0/35:case:code.3:15,10}{26681097sp}{33216951sp}
\tracepos{0/35:case:code.2:16,1}{27516683sp}{43949379sp}
\tracepos{0/35:case:code.2:16,1}{28222103sp}{43243959sp}
\tracepos{0/35:case:code.2:16,2}{27516683sp}{42835267sp}
\tracepos{0/35:case:code.2:16,2}{28222103sp}{42129847sp}
\tracepos{0/35:case:code.2:16,3}{27516683sp}{41721155sp}
\tracepos{0/35:case:code.2:16,3}{28222103sp}{41015735sp}
\tracepos{0/35:case:code.2:16,4}{27516683sp}{40607043sp}
\tracepos{0/35:case:code.2:16,4}{28222103sp}{39901623sp}
\tracepos{0/35:case:code.2:16,5}{27516683sp}{39492931sp}
\tracepos{0/35:case:code.2:16,5}{28222103sp}{38787511sp}
\tracepos{0/35:case:code.2:16,6}{27516683sp}{38378819sp}
\tracepos{0/35:case:code.2:16,6}{28222103sp}{37673399sp}
\tracepos{0/35:case:code.2:16,7}{27516683sp}{37264707sp}
\tracepos{0/35:case:code.2:16,7}{28222103sp}{36559287sp}
\tracepos{0/35:case:code.2:16,8}{27516683sp}{36150595sp}
\tracepos{0/35:case:code.2:16,8}{28222103sp}{35445175sp}
\tracepos{0/35:case:code.2:16,9}{27516683sp}{35036483sp}
\tracepos{0/35:case:code.2:16,9}{28222103sp}{34331063sp}
\tracepos{0/35:case:code.2:16,10}{27516683sp}{33922371sp}
\tracepos{0/35:case:code.2:16,10}{28222103sp}{33216951sp}
\tracepos{0/35:case:code.1:17,1}{29057689sp}{43949379sp}
\tracepos{0/35:case:code.1:17,1}{29763109sp}{43243959sp}
\tracepos{0/35:case:code.1:17,2}{29057689sp}{42835267sp}
\tracepos{0/35:case:code.1:17,2}{29763109sp}{42129847sp}

```

\tracepos{0/35:case:code.1:17,3}{29057689sp}{41721155sp}
\tracepos{0/35:case:code.1:17,3}{29763109sp}{41015735sp}
\tracepos{0/35:case:code.1:17,4}{29057689sp}{40607043sp}
\tracepos{0/35:case:code.1:17,4}{29763109sp}{39901623sp}
\tracepos{0/35:case:code.1:17,5}{29057689sp}{39492931sp}
\tracepos{0/35:case:code.1:17,5}{29763109sp}{38787511sp}
\tracepos{0/35:case:code.1:17,6}{29057689sp}{38378819sp}
\tracepos{0/35:case:code.1:17,6}{29763109sp}{37673399sp}
\tracepos{0/35:case:code.1:17,7}{29057689sp}{37264707sp}
\tracepos{0/35:case:code.1:17,7}{29763109sp}{36559287sp}
\tracepos{0/35:case:code.1:17,8}{29057689sp}{36150595sp}
\tracepos{0/35:case:code.1:17,8}{29763109sp}{35445175sp}
\tracepos{0/35:case:code.1:17,9}{29057689sp}{35036483sp}
\tracepos{0/35:case:code.1:17,9}{29763109sp}{34331063sp}
\tracepos{0/35:case:code.1:17,10}{29057689sp}{33922371sp}
\tracepos{0/35:case:code.1:17,10}{29763109sp}{33216951sp}

Contents

1	Introduction	1
2	Samples	1
2.1	Standard layout	4
2.2	Separate answer sheet	5
2.3	Without markers	7
3	Usage	11
3.1	Package options	11
3.2	Questions and answers	12
3.3	Scoring	13
3.4	Groups of questions	13
3.5	Students identification	14
3.6	Separate answer sheet	15
3.7	Random computation questions	15
3.8	French command names	16
3.9	Customisation	17
3.9.1	Boxes	17
3.9.2	Codes	17
3.9.3	Answers	18
4	Implementation	18
4.1	Variables	19
4.2	Dimensions	20
4.3	Localisation	21
4.3.1	English	21
4.3.2	French	21
4.3.3	Spanish	22
4.3.4	Other languages	22
4.4	Random	22
4.4.1	Random pseudo-generator	22
4.4.2	Uniform random deviates	22
4.4.3	Tokens shuffling	23
4.5	Keys numbering	23
4.6	Boxes	24
4.6.1	Position logging	24
4.6.2	Boxes to be checked by students	25
4.6.3	Binary boxes	27
4.7	Handling groups of questions	28
4.8	Questions	29
4.8.1	Managing answers	30
4.8.2	Separate answer sheet	31
4.8.3	Formatting answers	32
4.8.4	Formatting questions	33
4.9	Scoring	34

4.10	Codes	35
4.10.1	Intervals	37
4.11	Page formatting	37
4.11.1	Watermark	37
4.11.2	Signs for scan analysis	38
4.12	Defining a single exam copy content	39
4.13	Package options	40
4.14	Optional features	40
4.15	External control	41
4.16	Page layout	41
4.17	Initialisation	42
4.18	French command names	42
5	Outputs	43
5.1	namefield command	43
5.2	AMCboxedchar command	43
5.3	AMCcode command	43

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols		
\@aucune	327, 331, 332	\AMC@NCBetud . . . <u>214</u> , 544, 600
\@tempboxa	508, 512, 513	\AMC@NCBpage . . . <u>214</u> , 546, 600
\@tempdimb	497, 499	\AMC@note 523, 554, 651
\@tempdimc	498, 499	\AMC@numerotation 110, 114, 115
		\AMC@pagepos <u>118</u> , 526
		\AMC@premierecopie
		.. 219, 561, 563, 564, 602
A		\AMC@prepare . . . 113, 116, 117
\alafin	<i>13</i> , 681	\AMC@prepare@element
\AMC@affiche	<u>110</u> , 400	.. 253, 261, 291
\AMC@amclog . . . <u>7</u> , 111, 354,		\AMC@qaff <u>391</u> , 404, 417
383, 388, 411, 419–		\AMC@shuffletoks <u>96</u> , 265, 307
422, 560, 568, 659–662		\AMC@SR 65, 67, 70–73, 75, 77, 78
\AMC@binaryBoxes		\AMC@SR@count 70,
.. 220, 544, 546, 547		71, 73, 81, 85, 88, 91–94
\AMC@boxedchar . . <u>159</u> , 173,		\AMC@SR@time 82, 585
186, 188, 210, 226, 228		\AMC@SRadvance 68, 75, 76
\AMC@boxeddim 163, 164, 178, 179		\AMC@SRbit 75
\AMC@boxeddown . 161, 177, 181		\AMC@SRconst 66, 70, 73
\AMC@boxedrule . 160, 176, 180		\AMC@SRmax <u>81</u> , 105
\AMC@caselettre <u>166</u> , 204, 208		\AMC@SRnextByte <u>81</u>
\AMC@CBtaille . . 218, 542, 601		\AMC@SRnum 83,
\AMC@chiffres . . 423, 438,		84, 86, 87, 91, 94, 105, 106
439, 453, 465, 466, 480		\AMC@SRset 67, 79, 80, 82
\AMC@CI@a . . 484, 489, 490, 492		\AMC@SRtest 76, 87
\AMC@CI@b . . 487, 488, 490–492		\AMC@SRvalue 78
\AMC@CI@cas . 482, 485, 488, 489		\AMC@sti 96, 103–105, 107, 108
\AMC@definitnumero . . 111, 115		\AMC@tmpXY 152, 155, 157
\AMC@fin@rep <u>314</u> , 362, 366, 370		\AMC@tracebox . . <u>118</u> , 158, 518
\AMC@formBox <u>184</u>		\AMC@tracepos . . 118, 163, 165
\AMC@intervx 482, 490		\AMC@traceposx 126, 144
\AMC@intituleHead 522, 534, 596		\AMC@traceposy . . 134, 143, 145
\AMC@loc@catalog . 53, 62, 596		\AMC@unnumero <u>110</u>
\AMC@loc@corrected 52, 61, 522		\AMC@VERSION 6, 666
\AMC@loc@draft . . 47, 56, 495		\AMC@watertext 495, 506
\AMC@loc@FR 55, 597, 676		\AMC@XYFILE . 120, 128, 136,
\AMC@loc@message . 48, 57, 652		147, 155–157, 664–666
\AMC@loc@none . . . 54, 63, 327		\AMC@XYspecial
\AMC@loc@q 51, 60, 394		.. 151, 154, 156, 157
\AMC@loc@qf 50, 59, 335		\AMCanswer . 378, <u>379</u> , 434, 461
\AMC@logfile 7–9		\AMCbeginAnswer
\AMC@LR 369, <u>379</u> , 430, 459
<u>11</u> , 159, 500, 537–541, 652		\AMCbeginQuestion
\AMC@marque . <u>184</u> , 385, 386, 389		.. <u>394</u> , 404, 417, 428, 457
\AMC@NCBcheck . . <u>214</u> , 547, 601		
		\AMCbin@begin 229, 543, 545, 547
		\AMCbin@digit 224–229
		\AMCbin@id . 223, 226, 228, 229
		\AMCbin@endigits
		.. 222, 232, 235, 241
		\AMCbin@number
		.. 221, 231, 234, 236, 238
		\AMCbin@one 225, 236
		\AMCbin@sequence . . . 220,
		231, 236, 237, 242, 243
		\AMCbin@zero . . . 227, 237, 242
		\AMCbloc 398
		\AMCboxDimensions <i>13</i> , <u>176</u> , 231
		\AMCBoxedAnswers <u>356</u>
		\AMCcercle 514, 517
		\AMCchoiceLabel . . . <u>166</u> , 193
		\AMCcleasedoublepage . <i>11</i> , <u>571</u>
		\AMCcode <i>10</i> , <u>423</u>
		\AMCcodeBoxSep . 426, 435, 462
		\AMCcodeH <i>10</i> , <u>423</u>
		\AMCcodeHspace
		.. 424, 433, 454, 463
		\AMCcodeVspace
		.. 425, 432, 436, 460
		\AMCdebutFormulaire . <i>13</i> , 683
		\AMCdum@reponses . . <u>307</u> , 321
		\AMCendAnswer 370, <u>379</u> , 432, 460
		\AMCform <i>11</i> , <u>339</u> , 682
		\AMCformAnswer <u>334</u>
		\AMCformAnswerA . . . 338, 346
		\AMCformBegin . . . <i>11</i> , <u>339</u> , 683
		\AMCformBox <u>184</u>
		\AMCformHspace <u>42</u> , 337
		\AMCformQuestion <u>334</u>
		\AMCformQuestionA . . 336, 347
		\AMCforms <u>339</u>
		\AMCformVSpace <u>42</u> , 335
		\AMCid@check 17, 149,
		524, 525, 547, 550, 658
		\AMCid@checkmax
		.. <u>214</u> , 525, 600, 658
		\AMCid@etud 18, 122,
		130, 138, 149, 544, 550,
		561, 568, 569, 572–574

\AMCid@etudfin 19, 562–564, 569
\AMCid@name
41, 199, 202, 208, 210, 400
\AMCid@quest 16, 199,
202, 208, 210, 400, 401
\AMCinterBrep 42, 374
\AMCinterIrep 42, 360
\AMCintervals ... 12, 482, 685
\AMClabel 573
\AMCload@reponse
..... 318, 320, 385, 389
\AMCload@counter
... 15, 296–299, 302,
303, 307, 310–313, 316
\AMCload@reponse ... 301, 320
\AMCmem@ireAJ 339
\AMCmem@ireAJRep
... 345, 371, 375, 376, 378
\AMCmem@ireData
... 334, 343, 350, 351, 354
\AMCmem@ireQ 347, 406
\AMCmessage 7, 401, 407
\AMCnobloc 397, 437, 464
\AMCNombreCopies ... 558, 559
\AMCnum@copies 20, 558–560, 562
\AMCnum@questions .. 308, 310
\AMCnumero 392, 567
\AMCquestionaff 391
\AMCrandomseed 79
\AMCref 573
\AMCrep@count . 322, 324, 326
\AMCrep@bloc 359, 371
\AMCrep@count 199,
202, 208, 210, 295, 304,
324, 326, 330, 358, 364,
368, 382, 383, 386–389
\AMCrep@fini 318, 321, 325, 333
\AMCrep@init 314, 361, 364, 368
\AMCrep@itemize 358, 371
\AMCrep@ligne 364, 371
\AMCrep@o 315, 317
\AMCrep@perso 368, 371
\AMCrep@r 319
\AMCrien@deux 301, 318
\AMCsw@p 96
\AMCsw@p@ 97, 99, 101
\AMCtext 46
\AMCtok@ik 267, 273, 275–
277, 288, 290, 292, 293
\AMCtok@k 245, 256–258, 262, 292
\AMCtok@max 246, 269–
271, 277, 284–286, 293
\AMCw@termark 494, 527
\AMCw@terprint 494, 527
amcxyfile (environment) . 151
answers (option) 7

B
\bareme 13, 673
\baremeDefautM 13, 674
\baremeDefautS 13, 675
bloc (option) 13
\bonne 13, 671
box (option) 7

C
calibration (option) 5, 7
\CalibrationExterne 623
catalog (option) 8
\champnom 13, 684
chiffres (option) 13
\choices 668
choices (environment) . 8, 356
\choicescustom 670
choicescustom (environ-
ment) 8, 356
\choiceshoriz 669
choiceshoriz (environment)
..... 8, 356
\choixIntervalles .. 13, 685
\cleargroup 10, 279
completemulti (option) ... 7
\copieexamen 678
copieexamen (environment) . 13
\copygroup 10, 279
correc (option) 13
correcindiv (option) 13
\correctchoice
... 9, 332, 382, 488, 671
\CorrigeExterne 623
\CorrigeIndivExterne ... 623

D
digits (option) 7

E
\element 9, 245
\endchoices 668
\endchoicescustom 670
\endchoiceshoriz 669
\endcopieexamen 678
\endexamcopy 678
\endreponses 668
\endreponseshoriz 669
\endreponsesperso 670
ensemble (option) 13
environments:
amcxyfile 151
choices 8, 356
choicescustom 8, 356
choiceshoriz 8, 356
copieexamen 13
examcopy 615
question 8, 396
questionmult 8, 396
questionouverte 396
reponses 13
reponseshoriz 13
reponsesperso 13
\examcopy 678
examcopy (environment) .. 615
\exemplaire 13, 676
\exemplairepair 572

F
\formulaire 13, 682
francais (option) 8

H
\he@dbas 520, 537, 538
\he@dhaut 521, 541
\he@dtaille 519–521

I
\ifAMC@affichekeys 23, 403, 404
\ifAMC@calibration
..... 28, 119, 127,
135, 147, 383, 388, 401,
410, 419–422, 568, 663
\ifAMC@correc 24, 385
\ifAMC@correthead
22, 527, 533, 564, 644, 650
\ifAMC@ensemble
..... 35, 197, 340,
350, 353, 434, 461, 659
\ifAMC@inside@box
... 33, 207, 435, 462, 660
\ifAMC@inside@digit . 36, 167
\ifAMC@ordre 21, 315
\ifAMC@outside@box 34, 185, 661
\ifAMC@pagelayout
..... 39, 524, 530, 643

<code>\ifAMC@plain</code>	29, 607	<code>bloc</code>	13	<code>questionouverte</code> (environ- ment)	396
<code>\ifAMC@postcorrect</code>	40, 332, 662	<code>box</code>	7	R	
<code>\ifAMC@qbloc</code>		<code>calibration</code>	5, 7	<code>\reponses</code>	668
..	25, 402, 407, 416, 418	<code>catalog</code>	8	<code>reponses</code> (environment) . . .	13
<code>\ifAMC@rbloc</code>	26, 359, 362	<code>chiffres</code>	13	<code>\reponseshoriz</code>	669
<code>\ifAMC@watermark</code>	32, 527, 649	<code>completemulti</code>	7	<code>reponseshoriz</code> (environ- ment)	13
<code>\ifAMC@zoneformulaire</code> ..		<code>correc</code>	13	<code>\reponsesperso</code>	670
.....	38, 198, 340	<code>correcindiv</code>	13	<code>reponsesperso</code> (environ- ment)	13
<code>\ifAMC@complete@multi</code>	27, 329	<code>digits</code>	7	<code>\restituegroupe</code>	13, 680
<code>\ifAMC@formulaire@dedans</code>		<code>ensemble</code>	13	S	
.....	37, 201	<code>francais</code>	8	<code>\scoring</code> . 9, <u>419</u> , 440, 467, 673	
<code>\ifAMC@type@multi</code> . . .	31, 329	<code>indivanswers</code>	7	<code>\scoringDefaultM</code> . 9, <u>419</u> , 674	
<code>\ifAMC@une@bonne</code>	30, 331	<code>init</code>	7	<code>\scoringDefaultS</code> . 9, <u>419</u> , 675	
<code>indivanswers</code> (option)	7	<code>insidebox</code>	7	<code>separateanswersheet</code> (op- tion)	5, 7, 11
<code>init</code> (option)	7	<code>nopage</code>	7, 8	<code>\shuffle@it</code>	307, 321
<code>\insertgroup</code>	9, <u>264</u> , 680	<code>noshuffle</code>	7	<code>\shufflegroup</code>	9, <u>264</u> , 679
<code>insidebox</code> (option)	7	<code>nowatermark</code>	5, 7	<code>\SujetExterne</code>	<u>623</u>
L		<code>ordre</code>	13	T	
<code>\lastchoices</code>	<u>314</u> , 681	<code>outsidebox</code>	7	<code>\textsc</code>	534
M		<code>plain</code>	8	<code>\tracepos</code>	121, 129, 137
<code>\m@rque</code>	518, 537–540	<code>postcorrect</code>	8	U	
<code>\m@rqueCalage</code>	517, 518	<code>separateanswersheet</code> .		<code>\une@rep</code>	358, 359, 364, 368, 385, 389
<code>\mauvaise</code>	13, 672	5, 7, 11	V	
<code>\melangegroupe</code>	13, 679	<code>ordre</code> (option)	13	<code>\version</code>	666
<code>\multiSymbole</code>	<u>394</u> , 409	<code>outsidebox</code> (option)	7	W	
N		<code>\ouverte@vs</code>	<u>396</u>	<code>\wrongchoice</code>	9, 331, 332, <u>382</u> , 441–450, 468–477, 485, 489, 672
<code>\namefield</code>	10, <u>158</u> , 684	P			
<code>nopage</code> (option)	7, 8	<code>plain</code> (option)	8	Q	
<code>noshuffle</code> (option)	7	<code>postcorrect</code> (option)	8	<code>\question</code>	396
<code>\nouveaugroupe</code>	<u>245</u> , 280	Q			
<code>nowatermark</code> (option)	5, 7	<code>question</code> (environment)	8, <u>396</u>	W	
<code>\NoWatermarkExterne</code>	<u>623</u>	<code>\QuestionIndicative</code>		W	
O		9, <u>419</u> , 439, 466	W	
<code>\onecopy</code>	<u>557</u> , 619, 676	<code>questionmult</code> (environment)	8, <u>396</u>	W	
options:		Q			
<code>answers</code>	7	<code>\question</code>	396	W	